

## 1020-1120/1310~1650nm Fused WDM Coupler

### FEATURES

- Low Excess Loss
- Variety Coupling Ratio
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

### APPLICATIONS

- LAN WAN Systems
- Signal Monitoring
- Network Monitoring
- Research Labs
- Test Equipments



### SPECIFICATIONS

Parameter	Unit	Value
Wavelength Range Channel 1 ( $\lambda_1$ )	nm	1020 $\pm$ 10, 1030 $\pm$ 10, 1040 $\pm$ 10, 1053 $\pm$ 10, 1064 $\pm$ 10, 1070 $\pm$ 10, 1080 $\pm$ 10, 1092 $\pm$ 10, 1120 $\pm$ 10, 1150 $\pm$ 10
Wavelength Range Channel 2 ( $\lambda_2$ )	nm	1310 $\pm$ 10, 1550 $\pm$ 10, 1590 $\pm$ 10, 1625 $\pm$ 10
Insertion Loss	dB	$\leq$ 0.8
Isolation	dB	$\geq$ 15
Optical Return Loss	dB	$\geq$ 40
Directivity	dB	$\geq$ 50
Fiber Type	-	HI1060 Fiber (H) or HI1060 Flex Fiber (F) SMF-28 Fiber or 8/125um DC Fiber NA=0.12 (M) 6/125um DC Fiber NA=0.18 (M1)
Fiber Tensile Load	N	5
Maximum Optical Power (CW)	mW	300
Operating Temperature	$^{\circ}$ C	0~50
Storage Temperature	$^{\circ}$ C	-40~85
Package Dimension	Stainless Steel Tube (SST) Metal Box	mm
		$\phi$ 3.0x <sup>L</sup> 60 for Bare Fiber
		$\phi$ 3.0x <sup>L</sup> 76 for 900um Loose Tube
		<sup>L</sup> 120x <sup>W</sup> 12x <sup>H</sup> 10 for 2mm/3mm Cable

**Note:** 1. Specifications are for device without connectors; Specifications may change without notice.

2. To add connectors, IL is 0.5dB higher, RL is 5dB lower.

3. 1020-1150nm transmits as low order modes in signal fiber.

4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

5. Package size may be different for different optical power and fiber type.

### ORDERING INFORMATION (PN)

FCLD- NN	NN	- N	(C)	(C)	- (C)	(C)	C	NN	-CC/CCC
Wavelength1	Wavelength2	Configuration	Mode	Fiber( $\lambda_1$ )	Package	Fiber (Com&A2)	Fiber Sleeve	Fiber Length	Connector Type
03=1030nm	15=1550nm	1= 1x2 Type	M= Mux	S=SMF-28 Fiber	M=Metal Box	H=HI1060 Fiber	B= Bare Fiber	05=0.5m	N=Without Connector
06=1064nm	13=1310nm	2= 2x2 Type	D= Demux	H=HI1060 Fiber	Blank for SST	M= 8/125 PMDC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
59=1590nm	09= 1092nm		Blank for Both	Blank for Same Fiber		F= HI1060 Flex Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
62=1625nm	12=1120nm					Blank for SMF-28 Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector