

## 460~690nm 1X6/2X6 Fused Fiber Splitter Module

### FEATURES

- ▣ Low Excess Loss
- ▣ Variety Coupling Ratio
- ▣ Epoxy-Free Optical Path
- ▣ High Reliability and Stability
- ▣ Low Profile Packaging

### APPLICATIONS

- ▣ LAN WAN Systems
- ▣ Signal Monitoring
- ▣ Network Monitoring
- ▣ CATV
- ▣ Test Equipments



### SPECIFICATIONS

Parameter	Unit	1X6/2X6	
Center Wavelength	nm	460, 488, 520, 532	635, 650, 660, 690
Passband Width	nm	+/-5	
Split Ratio	%	Even Split	
Insertion Loss	dB	≤10.3	
Uniformity	dB	≤2.2	
Optical Return Loss	dB	≥40	
Directivity	dB	≥50	
Fiber Type	-	460-HP Fiber	630-HP Fiber
Fiber Tensile Load	N	5	
Maximum Optical Power (CW)	mW	100	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	mm	L100xW80xH10	

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
  2. To add connectors, IL is 0.9dB higher, RL is 5dB lower.
  3. Only guarantee 30mW continuous wave (CW) power thru testing for connectors added.
  4. Devices for higher optical power or with other type fiber or consigned fiber are also available.
  5. Package size may be different for different optical power and fiber type.

### ORDERING INFORMATION (PN)

<b>FCLT</b>	-	<b>NNNN</b>	-	<b>NXN</b>	-	<b>C</b>		<b>NN</b>	-	<b>CC/CCC</b>
<i>Center Wavelength</i>				<i>Configuration</i>		<i>Fiber Sleeve</i>		<i>Fiber Length</i>		<i>Connector Type</i>
488- 488nm				1X6- 1x6 Type		B- Bare fiber		05-0.5m		N-Without Connector
532- 532nm				2X6- 2x6 Type		L- Loose Tube		10-1.0m		FC/APC=FC/APC Connector
635- 635nm						2- 2mm Cable		15-1.5m		LC/PC=LC/PC Connector
650- 650nm						3- 3mm Cable		20-2.0m		SC/UFC=SC/UFC Connector