

## 915nm 1X6/2x6 Fused Fiber Splitter Module

### FEATURES

- Low Excess Loss
- Variety Coupling Ratio
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

### APPLICATIONS

- LAN WAN Systems
- Signal Monitoring
- Network Monitoring
- CATV
- Test Equipments



### SPECIFICATIONS

Parameter	Unit	1X6/2x6
Center Wavelength	nm	915, 930, 940, 950
Passband Width	nm	+/-10
Insertion Loss	dB	≤10.3
PDL	dB	≤0.3
Uniformity	dB	≤1.8
Optical Return Loss	dB	≥40
Directivity	dB	≥50
Fiber Type	-	HI780C Fiber, HI1060 Fiber (H) or HI1060 Flex Fiber (F) 10/125um SC Fiber (E) or 10/125um DC Fiber (O)
Fiber Tensile Load	N	5
Maximum Optical Power (CW)	mW	300
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	mm	(L)100x(W)80x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
  2. To add connectors, IL is 0.7dB higher, RL is 5dB lower.
  3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
  4. Package size may be different for different optical power and fiber type.

### ORDERING INFORMATION (PN)

FCLT-	NNN	-	NXN	- (C)	C	NN	-CC/CCC
	Center Wavelength		Configuration	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
	915=915nm		1X6= 1x6 Type	H= HI1060 Fiber	B= Bare Fiber	05=0.5m	N=Without Connector
	930=930nm		2X6= 2x6 Type	E= 10/125SC Fiber	L= Loose Tube	10= 1.0m	FC/APC=FC/APC Connector
	940=940nm			O= 10/125DC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
	950=950nm			Blank for HI780C Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector