

1064nm Bandpass Filter

FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Laser Systems
- Research Labs



SPECIFICATIONS

Parameters	Unit	Value	
Center Wavelength	nm	1064	
Min. Pass Band Width @ 0.5dB	nm	0.5, 2.0, 5.0, 6.0, 9.0, 17.0	
Insertion Loss over Pass Band Wavelength	dB	≤1.2	
Stop wavelength (ASE)	0.5nm Bandwidth	nm	1000~1063&1065~1100
	2nm Bandwidth	nm	1000~1060&1068~1100
	5nm Bandwidth	nm	1000~1058&1070~1100
	6nm Bandwidth	nm	1000~1057&1071~1100
	9nm Bandwidth	nm	1000~1055&1073~1100
	17nm Bandwidth	nm	1000~1047&1081~1100
Stop Wavelength (ASE) Isolation	Standard	dB	≥25
	High Isolation	dB	≥45
ASE Direction	-	F: Forward, B: Backward, T: Two-way	
Configuration	-	D: 2-port, Y: 3-port, X: 4-port	
Optical Return Loss	dB	≥50	
Polarization Dependent Loss	dB	≤0.15	
Fiber Type	Input&Output	-	HI1060 Fiber or 10/125um SC Fiber (E) 10/125um DC Fiber (O), 15/130um DC Fiber (W) 20/130um DC Fiber (Q) or 25/250um DC Fiber (R)
	ASE Guide Out (Y/X Type)	-	Same Fiber or MM Fiber
Fiber Tensile Load	N		5
Max. Optical Power (CW, ASE+Signal)	mW		300
Operating Temperature	°C		0~50
Storage Temperature	°C		-40~85
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5xL35
	Metal Box	mm	L120x ^W 12x ^H 10

Note: 1. Specifications are for device without connectors; Specifications may change without notice.

2. To add connectors, IL is 0.5dB higher, RL is 5dB lower.

3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

4. Package size may be different for different optical power and configurations.

ORDERING INFORMATION (PN)

FFBP-1064-NN(C)	(C)	(C)	(C)	-(C)	(C)	C	NN	-CC/CCC	
Bandwidth	ASE Type	ASE Iso	Fwd ASE Fiber	Rwd ASE Fiber	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
05=0.5nm	B=Backward	I=High	Y=Same Fiber	Y=Same Fiber	M=Metal Box	E=10/125 SC Fiber	B= Bare fiber	05=0.5m	N=Without Connector
20=2nm	T=Two-way	Isolation	A=105/125um Fiber	A=105/125um Fiber	Blank for SST	Q=20/130 DC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
90=9nm	Blank for Forward	Blank for	N=None	S=50/125um Fiber		R=25/250 DC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
170=17nm		Standard	Blank for D Type	Blank for None or D Type		Blank for HI1060 Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector

