

# 1599nm Bandpass Filter

## FEATURES

- High Isolation
- Low Insertion Loss
- Various Bandwidth
- High Reliability and Stability

## APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Research Labs



## SPECIFICATIONS

Parameters	Unit	Value
Center Wavelength	nm	1599
Min. Pass Band Width @ 0.5dB	nm	13.0
Insertion Loss over Pass Band Wavelength	dB	≤1.2
Stop Band @ 25dB	nm	1500~1586 & 1612~1650
ASE Direction	-	F: Forward, B: Backward, T: Two-way
Configuration	-	D: 2-port, Y: 3-port, X: 4-port
Optical Return Loss	dB	≥50
Polarization Dependent Loss	dB	≤0.1
Fiber Type	Input&Output	SMF-28 Fiber or 10/130um DC Fiber (O) 12/130um DC Fiber (T) or 20/130um DC Fiber (Q) 25/250um DC Fiber (R) or 25/300um DC Fiber (G)
	ASE Guide Out (Y/X Type)	Same Fiber or MM Fiber
Fiber Tensile Load	N	5
Max. Optical Power (CW, ASE+Signal)	mW	300
Operating Temperature	°C	0~70
Storage Temperature	°C	-40~85
Package Dimension	Stainless Steel Tube (SST)	mm (Ø)5.5x35
	Metal Box	mm (L)120x(W)12x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
  2. To add connectors, IL is 0.3dB higher, RL is 5dB lower.
  3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

## ORDERING INFORMATION (PN)

FFBP-1599-NNN(C)	(C)	(C)	-(C)	(C)	C	NN	-CC/CCC	
Bandwidth	ASE Type	Fwd ASE Fiber	Bwd ASE Fiber	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
130=13nm	B=Backward T=Two-way Blank for Forward	Y=Same Fiber A=105/125um Fiber N=None Blank for D Type	Y=Same Fiber A=105/125um Fiber 5=50/125um Fiber Blank for None or D Type	M=Metal Box Blank for SST	O=10/130 DC Fiber T=12/130 DC Fiber G=25/300 DC Fiber Blank for SMF-28 Fiber	B= Bare fiber L= Loose Tube 2= 2mm Cable 3= 3mm Cable	05=0.5m 10=1.0m 15=1.5m 20=2.0m	N=Without Connector FC/APC=FC/APC Connector LC/PC=LC/PC Connector SC/UPC=SC/UPC Connector