

## 1625~1650nm Faraday Mirror for Pulse Power

### FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- Low Polarization Sensitivity
- Low Profile Packaging

### APPLICATIONS

- Fiber Optic Amplifiers
- Sensing Systems
- Telecommunication Networks
- CATV Networks
- LAN Systems

### SPECIFICATIONS

Parameter	Unit	Value	
Center Wavelength ( $\lambda_c$ )	nm	1625, 1650	
Bandwidth	nm	+/-10	
Insertion Loss	(Typ.)	0.6	
	(Max.)	1.0	
Faraday Rotation Angle (Single Pass)	Deg	22.5, 45, 90	
Rotation Angle Tolerance (23°C, $\lambda_c$ +/-15nm)	Deg	$\leq$ +/-5	
Polarization Dependent Loss (SM Fiber Type)	dB	$\leq$ 0.10	
Extinction Ratio (PM Fiber Type)	ps	$\geq$ 18	
Fiber Type	SM Fiber Type	SMF-28 Fiber or 10/130um DC Fiber (O) 12/130um DC Fiber (T) or 20/130um DC Fiber (Q) 25/250um DC Fiber (R) or 25/300um DC Fiber (G)	
	PM Fiber Type	PM1310/1550 Panda Fiber or 10/125um PMDC Fiber (O) 12/130um PMDC Fiber (T), 20/130um PMDC Fiber (Q) 25/250um PMDC Fiber (R) or 25/300um PMDC Fiber (G)	
Fiber Tensile Load	N	5	
Max. Average Optical Power	W	0.3, 0.5, 1, 2, 3, 5, 10	
Max. Peak Power for Pulse	kW	0.1, 1, 2, 3, 5, 10, 15, 20	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	( $\varnothing$ )5.5x35 ( $\leq$ 5W); ( $\varnothing$ )6.0x48 (5~10W)
	Metal Box	mm	(L)120x(W)12x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
  2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
  3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
  4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

### ORDERING INFORMATION (PN)

FFDM-NNNN-(NN)	-H NN	P NN	- C	(C)	(C)	C	NN	-CC/CCC	
Center Wavelength	Rotation Angle	Average Power	Peak Power	Type	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
1625-1625nm	90-90degree	03-300mW	01-100W	P- PM Fiber	M-Metal Box	O=10/130DC or 10/125PMDC Fiber	B= Bare fiber	05=0.5m	N=Without Connector
1650-1650nm	225-22.5degree Blank for 45degree	1-1W	1-1kW	S-SM Fiber	Blank for SST	T=12/130DC or PMDC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
		5-5W	5-5kW			G=25/300 DC or PMDC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
		10-10W	10-10kW			Blank for SMF-28 Fiber or PM1550 Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector