

1625-1650nm High Power Faraday Mirror

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- Low Polarization Sensitivity
- Low Profile Packaging

APPLICATIONS

- Fiber Optic Amplifiers
- Sensing Systems
- Telecommunication Networks
- CATV Networks
- LAN Systems

SPECIFICATIONS

Parameter	Unit	Value	
Center Wavelength (λ_c)	nm	1625, 1650	
Bandwidth	nm	+/- 10	
Insertion Loss	(Typ.)	dB	0.6
	(Max.)	dB	1.0
Faraday Rotation Angle (Single Pass)	Deg	22.5, 45, 90	
Rotation Angle Tolerance (23°C, λ_c +/- 15nm)	Deg	\leq +/- 5	
Polarization Dependent Loss (SM Fiber Type)	dB	\leq 0.10	
Extinction Ratio (PM Fiber Type)	ps	\geq 18	
Fiber Type	SM Fiber Type	-	SMF-28 Fiber or 10/130um DC Fiber (O) 12/130um DC Fiber (T) or 20/130um DC Fiber (Q) 25/250um DC Fiber (R) or 25/300um DC Fiber (G)
	PM Fiber Type	-	PM1310/1550 Panda Fiber or 10/125um PMDC Fiber (O) 12/130um PMDC Fiber (T), 20/130um PMDC Fiber (Q) 25/250um PMDC Fiber (R) or 25/300um PMDC Fiber (G)
Fiber Tensile Load	N	5	
Maximum Optical Power (CW)	W	1, 2, 3, 5, 10	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	(\varnothing)5.5x35 (\leq 5W); (\varnothing)6.0x48 (5~10W)
	Metal Box	mm	(L)120x(W)12x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FFDM-NNNN	-	(NN)	-HP NN	-	C	(C)	(C)	C	NN	-	CC/CCC
<i>Center Wavelength</i>		<i>Rotation Angle</i>	<i>Optical Power</i>	<i>Fiber Type</i>	<i>Package</i>	<i>Fiber Type</i>		<i>Fiber Sleeve</i>	<i>Fiber Length</i>		<i>Connector Type</i>
1625- 1625nm		90= 90degree	1= 1W	P= PM Fiber	M= Metal Box	O=10/130DC or 10/125PMDC Fiber		B= Bare Fiber	05=0.5m		N=Without Connector
1650- 1650nm		225=22.5degree	2=2W	S=SM Fiber	Blank for SST	T=12/130DC or PMDC Fiber		L= Loose Tube	10=1.0m		FC/APC=FC/APC Connector
		Blank for 45degree	5=5W			G=25/300 DC or PMDC Fiber		2= 2mm Cable	15=1.5m		LC/PC=LC/PC Connector
			10=10W			Blank for SMF-28 Fiber or PM1550 Fiber		3= 3mm Cable	20=2.0m		SC/UPC=SC/UPC Connector

