

## 1092~1160nm High Power Filter Coupler

### FEATURES

- Low Excess Loss
- Various Splitting Ratio
- Wide Passband
- High Stability and Reliability
- Epoxy Free Optical Path

### APPLICATIONS

- Optical Amplifier
- Optical Networks
- Power Monitoring
- Fiber Sensor
- Lab



### SPECIFICATIONS

Parameter	Unit	1x2 Type			2x2 Type		
Center Wavelength	nm	1092, 1103, 1120, 1160					
Bandwidth	nm	+/-20nm or customer specify					
Split Ratio	-	1:99	2:98	5:95	10:90	40:60	50:50
Tap Ratio	-	1±0.5%	2±0.6%	5±1.0%	10%	40%	50%
Excess Loss	Max. dB	1.4			1.6		
Uniformity	Max. dB	1.0			1.4		
PDL	dB	≤0.15					
Optical Return Loss	dB	≥50					
Fiber Type	Tap Port	Same Fiber or 50/125um MM Fiber					
	Thru Port	HI1060 Fiber or 10/125um SC Fiber (E) 10/125um DC Fiber (O), 15/130um DC Fiber (W) 20/130um DC Fiber (Q) or 25/250um DC Fiber (R)					
Fiber Tensile Load	N	5					
Max. Optical Power (CW)	W	1, 2, 3, 5, 10, 15, 20, 30, 50, 60					
Operating Temperature	°C	0~50					
Storage Temperature	°C	-40~85					
Package	Stainless Steel Tube (SST)	mm	∅5.5x <sup>L</sup> 35 (≤5W); ∅6.0x <sup>L</sup> 50 (5~10W)				
Dimension	Metal Box	mm	<sup>L</sup> 90x <sup>W</sup> 12x <sup>H</sup> 10 (>10W); <sup>L</sup> 120x <sup>W</sup> 12x <sup>H</sup> 10 (≤10W)				

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
  2. To add connectors, IL is 0.5dB higher, RL is 5dB lower.
  3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
  4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
  5. Package size may be different for different optical power fiber type and configurations.

### ORDERING INFORMATION (PN)

FFFC- NNNN -	NN	N	(C)	-HP NN	-(C)	(C)	C	NN	-CC/CCC
Wavelength	Split Ratio	Type	Tap Port Fiber	Optical Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
1092~1092nm	01=1/99	1=1x2 Type	5=50/125um Fiber	1=1W	M=Metal Box	E=10/125 SC Fiber	B= Bare fiber	05=0.5m	N=Without Connector
1103~1103nm	05=5/95	2=2x2 Type	Blank for Same Fiber	2=2W	Blank for SST	Q=20/130 DC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
1120~1120nm	10=10/90			5=5W	or >10W	R=25/250 DC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
1150~1150nm	50=50/50			10=10W		Blank for HI1060 Fiber	3= 3mm Cable	20=2.0m	SC/UFC=SC/UFC Connector