

1620~1790nm Filter Coupler

FEATURES

- ▣ Low Excess Loss
- ▣ Various Splitting Ratio
- ▣ Wide Passband
- ▣ High Stability and Reliability
- ▣ Epoxy Free Optical Path

APPLICATIONS

- ▣ Optical Amplifier
- ▣ Optical Networks
- ▣ Power Monitoring
- ▣ Fiber Sensor
- ▣ Lab



SPECIFICATIONS

Parameter	Unit	Value					
Center Wavelength	nm	1625, 1650, 1700, 1730, 1750, 1790					
Bandwidth	nm	+/-20					
Split Ratio	-	1:99	2:98	5:95	10:90	40:60	50:50
Tap Ratio	-	1±0.5%	2±0.6%	5±1.2%	10%	40%	50%
Excess Loss	1x2	dB					
	2x2	≤1.2					
Uniformity	Max.	dB					
		≤1.4					
PDL		dB					
		≤0.2					
Optical Return Loss		dB					
		≥50					
Fiber Type	Tap Port	-	Same Fiber or 50/125um MM Fiber				
	Thru Port	-	SMF-28 Fiber or 10/130um DC Fiber (O) 12/130um DC Fiber (T) or 20/130um DC Fiber (Q) 25/250um DC Fiber (R) or 25/300um DC Fiber (G)				
Fiber Tensile Load		N	5				
Max. Optical Power (CW)		mW	300				
Operating Temperature		°C	0~50				
Storage Temperature		°C	-40~85				
Package	Stainless Steel Tube (SST)	mm	∅5.5xL35				
Dimension	Metal Box	mm	L120xW12xH10				

Note: 1. Specifications are for device without connectors; Specifications may change without notice.

2. To add connectors, IL is 0.3dB higher, RL is 5dB lower.

3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FFFC-NNNN	- NN	N	(C)	-(C)	(C)	C	NN	- CC/CCC
Wavelength	Split Ratio	Type	Tap Port Fiber	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
1625-1625nm	01-1/99	1-1x2	5-50/125um Fiber	M-Metal Box	O-10/130 DC Fiber	B- Bare fiber	05-0.5m	N-Without Connector
1700-1700nm	05-5/95	2-2x2	Blank for Same Fiber	Blank for SST	T-12/130 DC Fiber	L- Loose Tube	10-1.0m	FC/APC=FC/APC Connector
1730-1730nm	10-10/90				R-25/250 DC Fiber	2- 2mm Cable	15-1.5m	LC/PC=LC/PC Connector
1790-1790nm	50-50/50				Blank for SMF-28 Fiber	3- 3mm Cable	20-2.0m	SC/UPC=SC/UPC Connector