

2000nm Filter Coupler

FEATURES

- ▣ Low Excess Loss
- ▣ Various Splitting Ratio
- ▣ Wide Passband
- ▣ High Stability and Reliability
- ▣ Epoxy Free Optical Path

APPLICATIONS

- ▣ Optical Amplifier
- ▣ Optical Networks
- ▣ Power Monitoring
- ▣ Fiber Sensor
- ▣ Lab



SPECIFICATIONS

Parameter	Unit	Value					
Center Wavelength	nm	1900, 1950, 2000, 2050					
Bandwidth	nm	+/-20					
Split Ratio	-	1:99	2:98	5:95	10:90	40:60	50:50
Tap Ratio	-	1±0.5%	2±0.6%	5±1.2%	10%	40%	50%
Excess Loss	1x2	dB					
	2x2	dB					
Uniformity	Max.	dB					
PDL		dB					
Optical Return Loss		dB					
Fiber Type	Tap Port	-					
	Thru Port	-					
Fiber Tensile Load	N	5					
Max. Optical Power (CW)	mW	300					
Operating Temperature	°C	0~50					
Storage Temperature	°C	-40~85					
Package	Stainless Steel Tube (SST)	mm					
Dimension	Metal Box	mm					

Note: 1. Specifications are for device without connectors; Specifications may change without notice.

2. To add connectors, IL is 0.3dB higher, RL is 5dB lower.

3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FFFC-NNNN	- NN	N	(C)	- (C)	(C)	C	NN	- CC/CCC
Wavelength	Split Ratio	Type	Tap Port Fiber	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
1900-1900nm	01=1/99	1=1x2	5=50/125um Fiber	M=Metal Box	V=SM1950 Fiber	B= Bare fiber	05=0.5m	N=Without Connector
1950-1950nm	05=5/95	2=2x2	Blank for Same Fiber	Blank for SST	0=10/130 DC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
2000-2000nm	10=10/90				R=25/250 DC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
2050-2050nm	50=50/50				Blank for SMF-28 Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector