

900~950nm Optical Filter Coupler

FEATURES

- ▣ Low Excess Loss
- ▣ Various Splitting Ratio
- ▣ Wide Passband
- ▣ High Stability and Reliability
- ▣ Epoxy Free Optical Path

APPLICATIONS

- ▣ Optical Amplifier
- ▣ Optical Networks
- ▣ Power Monitoring
- ▣ Fiber Sensor
- ▣ Lab



SPECIFICATIONS

Parameter	Unit	1x2 Type			2x2 Type		
Center Wavelength	nm	915, 930, 940, 950					
Bandwidth	nm	+/-15nm or customer specify					
Split Ratio	-	1:99	2:98	5:95	10:90	40:60	50:50
Tap Ratio	-	1±0.5%	2±0.6%	5±1.0%	10%	40%	50%
Excess Loss	Max. dB	1.4			1.6		
Uniformity	Max. dB	1.0			1.4		
PDL	dB	≤0.20					
Optical Return Loss	dB	≥50					
Fiber Type	Tap Port	Same Fiber or 50/125um MM Fiber					
	Thru Port	HI780 Fiber, HI1060 Fiber or 10/125um SC Fiber (E) 10/125um DC Fiber (O), 15/130um DC Fiber (W) 20/130um DC Fiber (Q) or 25/250um DC Fiber (R)					
Fiber Tensile Load	N	5					
Max. Optical Power (CW)	mW	300					
Operating Temperature	°C	0~50					
Storage Temperature	°C	-40~85					
Package	Stainless Steel Tube (SST)	mm	∅5.5x ^L 35				
Dimension	Metal Box	mm	^L 120x ^W 12x ^H 10				

Note: 1. Specifications are for device without connectors; Specifications may change without notice.

2. To add connectors, IL is 0.7dB higher, RL is 5dB lower.

3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FFFC-	NNN	- NN	N	(C)	-(C)	(C)	C	NN	- CC/CCC
Wavelength	Split Ratio	Type	Tap Port Fiber	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type	
915~915nm	01=1/99	1=1x2 Type	5=50/125um Fiber	M=Metal Box	H=HI1060 Fiber	B= Bare fiber	05=0.5m	N=Without Connector	
930~930nm	05=5/95	2=2x2 Type	Blank for Same Fiber	Blank for SST	E=10/125 SC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector	
940~940nm	10=10/90				R=25/250 DC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector	
950~950nm	50=50/50				Blank for HI780 Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector	