

780~850/2000nm High Power WDM/Partial Mirror Hybrid

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Metro Networks
- CATV Networks



SPECIFICATIONS

Parameters	Unit	Value	
Signal Wavelength Range λ_1	nm	1900±10, 1930±20, 1950±20, 1970±20, 2000±30, 2030±20, 2050±10, 2070±10	
Pump Wavelength Range λ_2	nm	780+/-10, 793+/-10, 808+/-10, 830+/-10, 850+/-10	
Excess Loss Signal Channel@ λ_1	dB	≤1.5	
Insertion Loss Pump Channel@ λ_2	dB	≤1.3	
Signal Reflective Ratio (Common<->Pass)	%	1±0.6, 2±0.8, 5±1, 10, 20, 30, 40, 50, 60, 70, 80, 90	
Wavelength Signal Channel@ λ_2	dB	≥25	
Isolation Pump Channel@ λ_1	dB	≥12	
Optical Return Loss	dB	≥45	
PDL	dB	≤0.2	
Pump Type	Forward	-	Pump&Signal at same direction
	Backward	-	Pump&Signal at reverse direction
Fiber Type	Common & Signal Port	-	SMF-28 Fiber or SM1950 Fiber (V)
		-	10/130um DC Fiber (O) or 25/250um DC Fiber (R)
	Pump Port	-	Same Fiber, 780HP Fiber or HI780 Fiber
Fiber Tensile Load	N		5
Maximum Optical Power (CW)	W		1, 2, 3, 5, 10
Operating Temperature	°C		0~50
Storage Temperature	°C		-40~85
Package Dimension	Stainless Steel Tube (SST)	mm	(Ø)5.5x40 (≤5W); (Ø)6.0x48 (5~8W)
	Metal Box	mm	(L)90x(W)18x(H)10 (>8W); (L)120x(W)12x(H)10 (≤8W)

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.7dB higher, RL is 5dB lower.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FFHP-NN NN	- (C)	NN	(C)	-HP NN	- (C)	(C)	C	NN	-CC/CCC	
Refl. WL	Pass WL	Pump Type	Refl. Ratio	Pump Fiber	Optical Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
78~780nm	19~1950nm	F= Forward	01~1%	7~780HP Fiber	1~1W	M= Metal Box	V= SM1950 Fiber	B= Bare fiber	05=0.5m	N= Without Connector
79~793nm	90~1900nm	Blank for Backward	05~5%	H= HI780 Fiber	5~5W	Blank for SST	O= 10/130 DC Fiber	L= Loose Tube	10=1.0m	FC/APC= FC/APC Connector
81~808nm	20~2000nm		10~10%	Blank for Same Fiber	10~10W	or >8W	R= 25/250 DC Fiber	2= 2mm Cable	15=1.5m	LC/PC= LC/PC Connector
85~850nm	25~2050nm		50~50%		20~20W		Blank for SMF-28 Fiber	3= 3mm Cable	20=2.0m	SC/UPC= SC/UPC Connector