

Partial Reflective Fiber Mirror for Pulse Power

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- Low Polarization Sensitivity
- Low Profile Packaging

APPLICATIONS

- Fiber Optic Amplifiers
- Sensing Systems
- Telecommunication Networks
- CATV Networks
- LAN Systems

SPECIFICATIONS

Parameter	Unit	Value
Center Wavelength (CW)	nm	1310, 1480, 1550, 1590
Bandwidth	nm	+/-30
Excess Loss	dB	0.8
Nominal Reflective Ratio	%	1±0.5, 2±0.8, 5±1, 10±2, 50±8, 80, 90, 99
PDL (for SM Fiber Type)	dB	≤0.15
Extinction Ratio (for PM Fiber Type)	dB	≥18
Fiber Type	SM Fiber Type	SMF-28 Fiber or 10/130um DC Fiber (O) 12/130um DC Fiber (T) or 20/130um DC Fiber (Q) 25/250um DC Fiber (R) or 25/300um DC Fiber (G)
	PM Fiber Type	PM1310/1550 Panda Fiber or 10/125um PMDC Fiber (O) 12/130um PMDC Fiber (T), 20/130um PMDC Fiber (Q) 25/250um PMDC Fiber (R) or 25/300um PMDC Fiber (G)
Fiber Tensile Load	N	5
Max. Average Optical Power	W	0.3, 0.5, 1, 2, 3, 5, 10
Max. Peak Power for pulse	kW	0.1, 1, 2, 3, 5, 10, 15, 20
Operating Temperature	°C	0~70
Storage Temperature	°C	-40~85
Package Dimension	Stainless Steel Tube (SST)	mm (Ø)5.5x35 (≤5W); (Ø)6.0x48 (5~10W)
	Metal Box	mm (L)120x(W)12x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FFPF-NNNN - NN	C	C	-H NN	P NN	-(C)	(C)	C	NN	-CC/CCC	
Center Wavelength	Ref. Ratio	Input Fiber	Output Fiber	Average Power	Peak Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
1310-1310nm	01-1%	S=SM Fiber	S=SM Fiber	03-300mW	01-100W	M=Metal Box	O=10/130DC or 10/125PMDC Fiber	B= Bare Fiber	05-0.5m	N=Without Connector
1480-1480nm	10-10%	P= PM Fiber	P= PM Fiber	1- 1W	1- 1kW	Blank for SST	T=12/130DC or PMDC Fiber	L= Loose Tube	10-1.0m	FC/APC=FC/APC Connector
1550-1550nm	50-50%			5-5W	5-5kW		G=25/300 DC or PMDC Fiber	2= 2mm Cable	15-1.5m	LC/PC=LC/PC Connector
1590-1590nm	80-80%			10-10W	10-10kW		Blank for SMF-28 Fiber or PM1310/1550 Fiber	3= 3mm Cable	20-2.0m	SC/UPC=SC/UPC Connector