

## 1310~1590nm Partial Reflective Faraday Mirror for Pulse Power

### FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- Low Polarization Sensitivity

### APPLICATIONS

- Fiber Optic Amplifiers
- Sensing Systems
- Telecommunication Networks
- LAN Systems

### SPECIFICATIONS

Parameter	Unit	Value	
Center Wavelength (CW)	nm	1310, 1480, 1550, 1590	
Bandwidth	nm	+/-15	
Excess Loss	dB	≤1.0	
Nominal Reflective Ratio	%	1±0.5, 2±0.4, 5±1, 10±2, 50±8, 80, 90	
Faraday Rotation Angle (Transmission)	Deg	22.5, 45, 90	
Rotation Angle Tolerance (CW, 23°C)	Deg	≤+/-3	
Faraday Position	Forward Type	-	
	Backward Type	-	
		Faraday is before the Mirror	
		Faraday is after the Mirror	
PDL (for SM Fiber Type)	dB	≤0.15	
Extinction Ratio (for PM Fiber Type)	dB	≥18	
Fiber Type	SM Fiber Type	-	
		-	
		-	
	PM Fiber Type	-	
		-	
		-	
		SMF-28 Fiber or 10/130um DC Fiber (O)	
		12/130um DC Fiber (T) or 20/130um DC Fiber (Q)	
		25/250um DC Fiber (R) or 25/300um DC Fiber (G)	
		PM1310/1550 Panda Fiber or 10/125um PMDC Fiber (O)	
		12/130um PMDC Fiber (T), 20/130um PMDC Fiber (Q)	
		25/250um PMDC Fiber (R) or 25/300um PMDC Fiber (G)	
Fiber Tensile Load	N	5	
Max. Average Optical Power	W	0.3, 0.5, 1, 2, 3, 5, 10, 15, 20	
Max. Peak Power for pulse	kW	0.1, 1, 2, 3, 5, 10, 15, 20	
Operating Temperature	°C	0~70	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	
	Metal Box	mm	
			(Ø)5.5x35 (≤5W); (Ø)6.0x48 (5~10W)
			(L)90x(W)12x(H)10 (>10W); (L)120x(W)12x(H)10 (≤10W)

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
  2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
  3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
  4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

### ORDERING INFORMATION (PN)

FFPM-NNNN-NN (NN) - (C) C C -H NN P NN -(C) (C) C NN -CC/CCC

Center Wavelength	Ref. Ratio	Rotation Angle	Faraday	Input Fiber	Output Fiber	Average Power	Peak Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
1310-1310nm	01-1%	225-22.5degree	Position	S-SM Fiber	S-SM Fiber	03-300mW	01-100W	M-Metal Box	0-10/130DC	B- Bare Fiber	05-0.5m	N-Without Connector
1480-1480nm	10-10%	90-90degree	B-Backward	P- PM Fiber	P- PM Fiber	1- 1W	1- 1kW	Blank for SST or 10/125PMDC Fiber	L- Loose Tube	10-1.0m	FC/APC=FC/APC Connector	
1550-1550nm	50-50%	Blank for 45degree	Blank for Forward			5- 5W	5- 5kW		T-12/130DC or PMDC Fiber	2- 2mm Cable	15-1.5m	LC/PC=LC/PC Connector
1590-1590nm	80-80%					10-10W	10-10kW		G-25/300 DC or PMDC Fiber	3- 3mm Cable	20-2.0m	SC/UPC=SC/UPC Connector
									Blank for SMF-28 Fiber			
									or PM1310/1550 Fiber			