

## 750~850/1020~1150nm WDM Filter

### FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

### APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Metro Networks
- CATV Networks



### SPECIFICATIONS

Parameters		Unit	Standard	High Isolation
Pass Channel Wavelength Range $\lambda_1$		nm	750 $\pm$ 10, 780 $\pm$ 10, 793 $\pm$ 10, 810 $\pm$ 10, 830 $\pm$ 10, 850 $\pm$ 10,	
Reflective Channel Wavelength Range $\lambda_2$		nm	1020 $\pm$ 10, 1030 $\pm$ 10, 1040 $\pm$ 10, 1053 $\pm$ 10, 1064 $\pm$ 10, 1070 $\pm$ 10, 1080 $\pm$ 10, 1092 $\pm$ 10, 1120 $\pm$ 10, 1150 $\pm$ 10	
Insertion Loss	Pass Channel@ $\lambda_1$	dB	$\leq$ 1.6	$\leq$ 1.8
	Reflective Channel@ $\lambda_2$	dB	$\leq$ 1.6	
Configuration	Y Type	-	3-port	
	X Type	-	4-port (2x2 WDM)	
Isolation	Pass Channel@ $\lambda_2$	dB	$\geq$ 25	$\geq$ 45
	Reflective Channel@ $\lambda_1$	dB	$\geq$ 12	
Optical Return Loss		dB	$\geq$ 45	
Directivity		dB	$\geq$ 50	
Polarization Dependent Loss		dB	$\leq$ 0.2	
Fiber Type	Signal Fiber (1 $\mu$ m)	-	HI780 Fiber, 780-HP Fiber(7) or HI1060 Fiber(H) 10/125 $\mu$ m SC Fiber (E), 15/130 $\mu$ m DC Fiber (W) 20/130 $\mu$ m DC Fiber (Q) or 25/250 $\mu$ m DC Fiber (R)	
	Common & Pump	-	Same Fiber, 780-HP Fiber(7) or HI780 Fiber	
Fiber Tensile Load		N	5	
Maximum Optical Power (CW)		mW	300	
Operating Temperature		$^{\circ}$ C	0~50	
Storage Temperature		$^{\circ}$ C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	$\varnothing$ 5.5xL35	
	Metal Box	mm	L120xW12xH10	

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
  2. To add connectors, IL is 0.7dB higher, RL is 5dB lower.
  3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
  4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
  5. 750~850nm light will transmit as low order modes in HI1060 Fiber or LMA fiber.

### ORDERING INFORMATION (PN)

FFWM-NN	NN	(C)	(C)	(C)	(C)	-(C)	(C)	C	NN	-CC/CCC
Ref Wavelength	Pass Wavelength	Pump Fiber	Pump Fiber2	Comm. Fiber	Isolation	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
79-793nm	03-1030nm	S= Same Fiber	X= Same Fiber	Y= Same Fiber	I= High Iso	M= Metal Box	7= 780-HP Fiber	B= Bare Fiber	05=0.5m	N=Without Connector
83-830nm	09-1092nm	7= 780-HP Fiber	7= 780-HP Fiber	7= 780-HP Fiber	Blank for	Blank for SST	H=HI1060 Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
06=1064nm	78=780nm	Blank for	H=HI780 Fiber	Blank for HI780 Fiber	Standard		R=25/250 DC Fiber	2=2mm Cable	15=1.5m	LC/PC =LC/PC Connector
12=1120nm	85=850nm	HI780 Fiber	Blank for Y Type				Blank for HI780 Fiber	3=3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector

