

750~850/1310~1650nm WDM Filter

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Metro Networks
- CATV Networks



SPECIFICATIONS

Parameters		Unit	Standard	High Isolation
Pass Channel Wavelength Range λ_1		nm	750 \pm 10, 780 \pm 10, 793 \pm 10, 810 \pm 10, 830 \pm 10, 850 \pm 10,	
Reflective Channel Wavelength Range λ_2		nm	1310 \pm 20, 1550 \pm 20, 1590 \pm 20, 1625 \pm 20, 1650 \pm 10	
Insertion Loss	Pass Channel@ λ_1	dB	\leq 1.8	\leq 2.0
	Reflective Channel@ λ_2	dB	\leq 1.8	
Configuration	Y Type	-	3-port	
	X Type	-	4-port (2x2 WDM)	
Isolation	Pass Channel@ λ_2	dB	\geq 25	\geq 45
	Reflective Channel@ λ_1	dB	\geq 12	
Optical Return Loss		dB	\geq 45	
Directivity		dB	\geq 50	
Polarization Dependent Loss		dB	\leq 0.2	
Fiber Type	Signal	-	780HP Fiber (7), HI780 Fiber (H) or SMF-28 Fiber 10/130um DC Fiber (O), 12/130um DC Fiber (T) 20/130um DC Fiber (Q), 25/300um DC Fiber (G)	
	Common & Pump	-	Same Fiber, 780-HP Fiber (7) or HI780 Fiber	
Fiber Tensile Load		N	5	
Maximum Optical Power (CW)		mW	300	
Operating Temperature		°C	0~50	
Storage Temperature		°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	\varnothing 5.5x ^L 35	
	Metal Box	mm	^L 120x ^W 12x ^H 10	

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.7dB higher, RL is 5dB lower.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 5. 750~850nm light may transmit as low order modes in SMF-28 Fiber or LMA fiber.

ORDERING INFORMATION (PN)

FFWM-NN	NN	-	(C)	(C)	(C)	(C)	- (C)	(C)	C	NN - CC/CCC
Ref Wavelength	Pass Wavelength	Pump Fiber	Pump Fiber2	Comm. Fiber	Isolation	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
79-793nm	15-1550nm	S= Same Fiber	X= Same Fiber	Y= Same Fiber	I= High Iso	M= Metal Box	H= HI780 Fiber	B= Bare Fiber	05=0.5m	N= Without Connector
83-830nm	59-1590nm	7= 780HP Fiber	7= 780HP Fiber	7= 780HP Fiber	Blank for	Blank for SST	O=10/130 DC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
13-1310nm	78-780nm	Blank for HI780 Fiber	H= HI780 Fiber	Blank for HI780 Fiber	Standard		T=12/130 DC Fiber	2=2mm Cable	15=1.5m	LC/PC=LC/PC Connector
15-1550nm	85-850nm		Blank for Y Type				Blank for SMF-28 Fiber	3=3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector