

1550nm BP/Partial Mirror Hybrid (<10nm BW)

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Metro Networks
- CATV Networks



SPECIFICATIONS

Parameters	Unit	Value	
Center Wavelength	nm	1550	
Min. Bandwidth@0.5dB	nm	0.3, 0.7, 2.0, 3.0, 4.0, 5.0, 7.0	
Excess Loss	dB	≤1.3	
Stop Band @25dB	0.3nm Bandwidth	1520~1549 & 1551~1610	
	0.7nm Bandwidth	1520~1548 & 1552~1610	
	2nm Bandwidth	1520~1547 & 1553~1610	
	3nm Bandwidth	1520~1546 & 1554~1610	
	4nm Bandwidth	1520~1545 & 1555~1610	
	5nm Bandwidth	1520~1544 & 1556~1610	
	7nm Bandwidth	1520~1543 & 1557~1610	
Reflective Ratio	%	1±0.6, 2±0.8, 5±1, 10, 20, 30, 40, 50, 80, 90	
Configuration	D Type	-	2-port
	Y Type	-	3-port, (Blocked Wavelength Guide Out)
Fiber Type at 3 rd Port (Only for Y Type)	-	-	Same Fiber or 50/125um MM Fiber
Optical Return Loss	dB	≥45	
PDL	dB	≤0.15	
Fiber Type	-	-	SMF-28 Fiber or 10/130um DC Fiber (O)
	-	-	12/130um DC Fiber (T) or 20/130um DC Fiber (Q)
	-	-	25/250um DC Fiber (R) or 25/300um DC Fiber (G)
Fiber Tensile Load	N	5	
Max. Optical Power (CW)	mW	300	
Operating Temperature	°C	0~70	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	(Ø)5.5x35
	Metal Box	mm	(L)120x(W)12x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower.
 3. Suggest to use Y type if blocked optical power is >1W.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FHBR-NNNN	- NN	NN	- (C)	- (C)	(C)	C	NN	-CC/CCC
Center Wavelength	Bandwidth	Ref. Ratio	3rd Port Fiber	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
1550=1550nm	03=0.3nm	01=1%	Y=Same Fiber	M=Metal Box	O=10/130 DC Fiber	B= Bare fiber	05=0.5m	N=Without Connector
	07=0.7nm	05=5%	5=50/125um Fiber	Blank for SST	T=12/130 DC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
	30=3nm	50=50%	Blank for D Type		G=25/300 DC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
	70=7nm	90=90%			Blank for SMF-28 Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector