



## 1560nm BP/Partial Mirror Hybrid

### FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

### APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Metro Networks
- CATV Networks

### SPECIFICATIONS

Parameters	Unit	Value	
Center Wavelength	nm	1560	
Min. Bandwidth@0.5dB	nm	1.0, 2.0, 5.0, 10.0, 15.0, 20.0	
Excess Loss	dB	≤1.3	
Stop Band @25dB	1nm Bandwidth	1520~1558.5 & 1561.5~1610	
	2nm Bandwidth	1520~1557.5 & 1562.5~1610	
	5nm Bandwidth	1520~1554 & 1566~1610	
	10nm Bandwidth	1520~1550 & 1570~1610	
	15nm Bandwidth	1520~1547 & 1573~1610	
	20nm Bandwidth	1520~1545 & 1575~1610	
Reflective Ratio	%	1±0.6, 2±0.8, 5±1, 10, 20, 30, 40, 50, 80, 90	
Configuration	D Type	2-port	
	Y Type	3-port, (Blocked Wavelength Guide Out)	
Fiber Type at 3 <sup>rd</sup> Port (Only for Y Type)	-	Same Fiber or 50/125um MM Fiber	
Optical Return Loss	dB	≥45	
PDL	dB	≤0.15	
Fiber Type	-	SMF-28 Fiber or 10/130um DC Fiber (O)	
	-	12/130um DC Fiber (T) or 20/130um DC Fiber (Q)	
	-	25/250um DC Fiber (R) or 25/300um DC Fiber (G)	
Fiber Tensile Load	N	5	
Max. Optical Power (CW)	mW	300	
Operating Temperature	°C	0~70	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	(Ø)5.5x35
	Metal Box	mm	(L)120x(W)12x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
  2. To add connectors, IL is 0.3dB higher, RL is 5dB lower.
  3. Suggest to use Y type if blocked optical power is >1W.
  4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

### ORDERING INFORMATION (PN)

FHBR-NNNN	-	NN	-	(C)	-	(C)	(C)	C	NN	-CC/CCC
Center Wavelength		Bandwidth		3rd Port Fiber		Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
1560=1560nm		10=1nm		Y=Same Fiber		M=Metal Box	O=10/130 DC Fiber	B= Bare fiber	05=0.5m	N=Without Connector
		50=5nm		5=50/125um Fiber		Blank for SST	T=12/130 DC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
		100=10nm		Blank for D Type			G=25/300 DC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
		200=20nm					Blank for SMF-28 Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector