

# 1040nm PBC(PBS)/Isolator Hybrid for Pulse Power

## FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

## APPLICATIONS

- Fiber Optic Amplifiers
- Fiber Optic Instruments
- WDM Systems
- Transmitters and Fiber Lasers
- CATV Networks



## SPECIFICATIONS

Parameter	Unit	Single Stage	Dual Stage	
Center Wavelength ( $\lambda_c$ )	nm	1040		
Bandwidth	nm	+/-10		
Peak Isolation (Typ.)	dB	28	50	
Isolation ( $\lambda_c$ +/-10nm, 23°C, All SOP)	dB	$\geq 22$	$\geq 45$	
Typical Insertion Loss ( $\lambda_c$ , 23°C, All SOP)	dB	2.6	4.3	
Insertion Loss ( $\lambda_c$ , 0-50°C, All SOP)	dB	$\leq 3.5$	$\leq 6.7$	
Optical Return Loss (Input/Output)	dB	50/50	50/50	
Extinction Ratio (for FHIS)	dB	$\geq 18$		
Fiber Type of Port 3	S Type	-	Corresponding SM Fiber	
	P Type	-	Same Fiber to Port1&2, Slow axis align to Port 1	
	Q Type	-	Same Fiber to Port1&2, Slow axis is 45° to Port 1	
Fiber Type of Port 1 & Port 2	-	PM980 Fiber, PM1060L Fiber (E) or PM1060L-FA Fiber (L) 10/125um PMDC Fiber (O), 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)		
Fiber Tensile Load	N	5		
Max. Average Optical Power	mW	100		
Max. Peak Power for pulse	kW	0.1, 1, 2, 3, 5, 10, 15, 20		
Operating Temperature	°C	0~50		
Storage Temperature	°C	-40~85		
Package Dimension	Stainless Steel Tube (SST)	mm	$(\varnothing)5.5 \times 35$	
	Metal Box	mm	$(L)120 \times (W)12 \times (H)10$	

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
  2. To add connectors, IL is 0.5dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
  3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
  4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

## ORDERING INFORMATION (PN) FHIC=PBC/Isolator Hybrid; FHIS=PBS/Isolator Hybrid.

FHIC FHIS	- NNNN	- C	C	-H NN	P NN	- (C)	C	C	NN	-CC/CCC
	Center Wavelength	Stage	3rd Port Fiber	Average Power	Peak Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
	1040=1040nm	S= Single Stage D= Dual Stage	S=S Type P=P Type Q=Q Type	01=100mW	01=100W 1= 1kW 5=5kW 10=10kW	M=Metal Box Blank for SST	2=PM980 Panda Fiber E=PM1060L Fiber Q=20/130 PMDC Fiber R=25/250 PMDC Fiber	B= Bare fiber L= Loose Tube 2= 2mm Cable 3= 3mm Cable	05=0.5m 10=1.0m 15=1.5m 20=2.0m	N=Without Connector FC/APC=FC/APC Connector LC/PC=LC/PC Connector SC/UPC=SC/UPC Connector