

## 1092nm Polarization Beam Combiner(Splitter)/Isolator Hybrid

### FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

### APPLICATIONS

- Fiber Optic Amplifiers
- Fiber Optic Instruments
- WDM Systems
- Transmitters and Fiber Lasers
- CATV Networks



### SPECIFICATIONS

Parameter	Unit	Single Stage	Dual Stage
Center Wavelength ( $\lambda_c$ )	nm	1092	
Bandwidth	nm	+/-10	
Peak Isolation (Typ.)	dB	25	45
Isolation ( $\lambda_c \pm 5\text{nm}$ , 23°C)	dB	$\geq 22$	$\geq 40$
Insertion Loss ( $\lambda_c$ , 23°C)	dB	1.7	2.6
Insertion Loss ( $\lambda_c$ , 0-50°C)	dB	$\leq 2.5$	$\leq 3.9$
Optical Return Loss (Input/Output)	dB	50/45	50/45
Extinction Ratio	dB	$\geq 20$	
Fiber Type of Port 3	S Type	-	Corresponding SM Fiber
	P Type	-	Same Fiber to Port1&2, Slow axis align to Port 1
	Q Type	-	Same Fiber to Port1&2, Slow axis is 45° to Port 1
Fiber Type of Port 1 & Port 2	-	PM980 Fiber, PM1060L Fiber (E) or PM1060L-FA Fiber (L) 10/125um PMDC Fiber (O), 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)	
Fiber Tensile Load	N	5	
Maximum Optical Power (CW)	mW	300	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	( $\varnothing$ )5.5x35
	Metal Box	mm	(L)120x(W)12x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
  2. To add connectors, IL is 0.5dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
  3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

### ORDERING INFORMATION (PN) FHIC=PBC/Isolator Hybrid; FHIS=PBS/Isolator Hybrid.

<b>FHIC</b>	<b>NNNN</b>	<b>-</b>	<b>C</b>	<b>-</b>	<b>(C)</b>	<b>C</b>	<b>C</b>	<b>NN</b>	<b>-</b>	<b>CC/CCC</b>	
<b>FHIS</b>	<i>Center Wavelength</i>		<i>Stage</i>		<i>3rd Port Fiber</i>	<i>Package</i>	<i>Fiber Type</i>	<i>Fiber Sleeve</i>		<i>Fiber Length</i>	<i>Connector Type</i>
	1092=1092nm		S= Single Stage		S=S Type	M= Metal Box	2=PM980 Panda Fiber	B= Bare fiber		05=0.5m	N=Without Connector
			D= Dual Stage		P=P Type	Blank for SST	E=PM1060L Fiber	L= Loose Tube		10=1.0m	FC/APC=FC/APC Connector
					Q=Q Type		Q=20/130 PMDC Fiber	2= 2mm Cable		15=1.5m	LC/PC=LC/PC Connector
							R=25/250 PMDC Fiber	3= 3mm Cable		20=2.0m	SC/UPC=SC/UPC Connector