

2030~2070nm High Power PBC(PBS)/Isolator Hybrid

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Fiber Optic Amplifiers
- Fiber Optic Instruments
- WDM Systems
- Transmitters and Fiber Lasers
- CATV Networks




SPECIFICATIONS

Parameter	Unit	Single Stage	Dual Stage	H Stage
Working Wavelength (λ)	nm	2030 \pm 20, 2050 \pm 20, 2070 \pm 10		
Isolation (λ , 23°C)	dB	≥ 16	≥ 30	≥ 25
Insertion Loss (λ , 23°C)	dB	≤ 1.6	≤ 1.9	≤ 1.9
Optical Return Loss (Input/Output)	dB	50/45	50/45	50/45
Extinction Ratio	dB	≥ 18		
Fiber Type of Port 3	S Type	-	Corresponding SM Fiber	
	P Type	-	Same Fiber to Port1&2, Slow axis align to Port 1	
	Q Type	-	Same Fiber to Port1&2, Slow axis is 45° to Port 1	
Fiber Type of Port1 & Port2	-	PM1550 Panda Fiber or PM1950 Fiber (V) 10/130um PMDC Fiber (O) or 25/250um PMDC Fiber (R)		
Fiber Tensile Load	N	5		
Maximum Optical Power (CW)	W	1, 2		3, 5, 10, 15, 20
Operating Temperature	°C	0~50		
Storage Temperature	°C	-20~75		
Package	Stainless Steel Tube (SST)	mm	Φ 5.5x35	
Dimension	Metal Box-M	mm	(L)120x(W)12x(H)10	
See Drawing				

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

PACKAGE DIMENSION (H STAGE)



ORDERING INFORMATION (PN) FHIC=PBC/Isolator Hybrid; FHIS=PBS/Isolator Hybrid.

FHIC FHIS	-NNNN	- C	C	-HP NN	-(C)	C	C	NN	-CC/CCC
	Center Wavelength	Stage	3rd Port Fiber	Optical Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
	2030- 2030nm	S- Single Stage	S=S Type	1-1W	M=Metal Box	2-PM1550Fiber	B= Bare fiber	05=0.5m	N=Without Connector
	2050- 2050nm	D- Dual Stage	P=P Type	2-2W	Blank for SST	V-PM1950 Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
	2070- 2070nm	H- H Stage	Q=Q Type	5-5W 10-10W	or >2W Power	O=10/130 PMDC Fiber R=25/250 PMDC Fiber	2= 2mm Cable 3= 3mm Cable	15=1.5m 20=2.0m	LC/PC=LC/PC Connector SC/UPC=SC/UPC Connector