

Optical Inline Polariser

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Fiber Optic Amplifiers
- Fiber Optic Instruments
- WDM Systems
- Dispersion Compensation
- Research Labs



SPECIFICATIONS

Parameter	Unit	Value	
Center Wavelength	nm	1310, 1480, 1550, 1590	
Bandwidth	nm	+/-30	
Insertion Loss @ 23°C	(Typ.)	dB	0.5
	(Max.)	dB	0.8
Extinction Ratio @ 23°C	(Typ.)	dB	28
	(Min.)	dB	25
Optical Return Loss	dB	≥50	
Configuration	D Type	-	2-port, Standard
	Y Type	-	3-port, Fast axis blocked light guide out
Fiber Type at 3 rd Port (Only for Y Type)	-	-	Same Fiber, Corr. SM Fiber or 50/125um MM Fiber
Fiber Type	SM Fiber	-	SMF-28 Fiber or 10/130um DC Fiber (O) 12/130um DC Fiber (T) or 20/130um DC Fiber (Q) 25/250um DC Fiber (R) or 25/300um DC Fiber (G)
	PM Fiber	-	PM1310/1550 Panda Fiber, 10/125um PMDC Fiber (O), 12/130um PMDC Fiber (T), 20/130um PMDC Fiber (Q) 25/250um PMDC Fiber (R), 25/300um PMDC Fiber (G)
Fiber Tensile Load	N		5
Max. Optical Power (CW)	mW		300
Operating Temperature	°C		0~70
Storage Temperature	°C		-40~85
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5x35
	Metal Box	mm	L120xW12xH10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 4. Package size may be different for different fiber type, configuration and optical power

ORDERING INFORMATION (PN)

FILP-NNNN	-	C	C	(C)	-	(C)	C	NN	-	CC/GCC
<i>Center Wavelength</i>		<i>Input Fiber</i>	<i>Output Fiber</i>	<i>3rd Port Fiber</i>	<i>Package</i>	<i>Fiber Type</i>	<i>Fiber Sleeve</i>	<i>Fiber Length</i>		<i>Connector Type</i>
1310-1310nm		P= PM Fiber	P= PM Fiber	P= Same Fiber	M= Metal Box	O=10/130 DC Fiber	B= Bare fiber	05=0.5m		N=Without Connector
1480-1480nm		S=SM Fiber	S=SM Fiber	S=Corr. SM Fiber	Blank for SST	T=12/130 DC Fiber	L= Loose Tube	10=1.0m		FC/APC=FC/APC Connector
1550-1550nm				5=50/125um MM Fiber	or >10W	G=25/300 DC Fiber	2= 2mm Cable	15=1.5m		LC/PC=LC/PC Connector
1590-1590nm				Blank for D Type		Blank for SMF-28 Fiber or PM1310/1550 Fiber	3= 3mm Cable	20=2.0m		SC/UPC=SC/UPC Connector