

## 915~990nm Multimode Optical Filter Coupler

### FEATURES

- Low Excess Loss
- Various Splitting Ratio
- Wide Passband
- High Stability and Reliability
- Epoxy Free Optical Path

### APPLICATIONS

- Optical Amplifier
- Optical Networks
- Power Monitoring
- Fiber Sensor
- Lab



### SPECIFICATIONS

Parameter	Unit	1x2 Type			2x2 Type		
Center Wavelength	nm	915, 930, 940, 950 975, 980, 990, 1000					
Bandwidth	nm	+/-15nm or customer specify					
Split Ratio	-	1:99	2:98	5:95	10:90	40:60	50:50
Tap Ratio	-	1±0.5%	2±0.6%	5±1.0%	10%	40%	50%
Excess Loss Max.	dB	1.2			1.5		
Uniformity Max.	dB	1.0			1.2		
Optical Return Loss	dB	≥35					
Fiber Type	-	50/125um or 62.5/125um MM Fiber 50/125um MM OM3 Fiber 105/125um MM Fiber					
Fiber Tensile Load	N	5					
Max. Optical Power (CW)	mW	300					
Operating Temperature	°C	0~70					
Storage Temperature	°C	-40~85					
Package	Stainless Steel Tube (SST)	mm	∅5.5xL35				
Dimension	Metal Box	mm	L120xW12xH10				

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
  2. To add connectors, IL is 0.3dB higher, RL is 10dB lower.
  3. Specifications are tested at low order modes.
  4. Devices with other wavelength range are also available per request.
  5. Devices for higher optical power or with other type fiber or consigned fiber are also available.

### ORDERING INFORMATION (PN)

FMFC - <b>NNN</b>	- <b>NN</b>	<b>N</b>	- ( <b>C</b> )	<b>C</b>	<b>C</b>	<b>NN</b>	- <b>CC/CCC</b>
Wavelength	Split Ratio	Type	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
915-915nm	01=1/99	1=1x2	M= Metal Box	5=50/125um MM Fiber	B= Bare Fiber	05=0.5m	N=Without Connector
930-930nm	05=5/95	2=2x2	Blank for SST	6= 62.5/125um MM Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
975-975nm	10=10/90			3= OM3 MM Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
990-990nm	50=50/50			A=105/125um NA=0.22	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector
				B=105/125um NA=0.15			