

915/1310/1550/1590nm Multimode WDM Filter

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Broadband Systems
- Optical Add/Drop Multiplexing
- Telecommunication Networks
- Metro Networks
- CATV Networks



SPECIFICATIONS

Parameters	Unit	Value	
Pass Channel Wavelength Range λ_1	nm	1310+/-20, 1550+/-20, 1590+/-20	
Reflective Channel Wavelength Range λ_2	nm	915+/-15	
Insertion Loss	Pass Channel@ λ_1	dB	≤ 1.2
	Reflective Channel@ λ_2	dB	≤ 1.0
Configuration	Y Type	-	3-port
	X Type	-	4-port (2x2 WDM)
Isolation	Pass Channel@ λ_2	dB	≥ 25
	Reflective Channel@ λ_1	dB	≥ 12
Optical Return Loss	dB	≥ 30	
Directivity	dB	≥ 35	
Fiber Type	-	50/125um or 62.5/125um MM Fiber 50/125um MM OM3 Fiber 105/125um MM Fiber	
Maximum Optical Power (CW)	mW	300	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	(\varnothing)5.5x35
	Metal Box	mm	(L)120x(W)12x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 10dB lower.
 3. Devices for higher optical power or with other type fiber or consigned fiber are also available.
 4. Specifications are tested at low order modes.
 5. Devices with other wavelength range are also available per request.

ORDERING INFORMATION (PN)

FMFM-	NN	NN	(C)	-	(C)	C	C	NN	-	CC/CCC
Ref Wavelength	Pass Wavelength	Configuration	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type			
91-915nm	15-1550nm	X= X Type	M= Metal Box	5- 50/125um MM Fiber	B= Bare Fiber	05=0.5m	N= Without Connector			
15-1550nm	91-915nm	Blank for Y Type	Blank for SST	6- 62.5/125um MM Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector			
59-1590nm	59-1590nm		or >10W	3- OM3 MM Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector			
13-1310nm	13-1310nm			A- 105/125um, NA=0.22 B- 105/125um, NA=0.15	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector			