

## 1032nm High Power PM Bandpass Filter

### FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

### APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Laser Systems
- Research Labs



### SPECIFICATIONS

Parameters	Unit	Standard	High ER Type	
Center Wavelength	nm	1032		
Min. Pass Band Width @ 0.5dB	nm	5.0		
Insertion Loss over Pass Band Wavelength	dB	≤1.2	≤1.4	
Stop Wavelength (ASE)	nm	960~1026&1038~1100		
Stop Wavelength (ASE) Standard	dB	≥25		
Isolation High Isolation	dB	≥45		
ASE Direction	-	F: Forward, B: Backward, T: Two-way		
Configuration	-	D: 2-port, Y: 3-port, X: 4-port		
Optical Return Loss	dB	≥50		
Extinction Ratio	dB	≥18	≥20	
Fiber Type	Input&Output	PM980 Fiber, PM1060L Fiber (E) or PM1060L-FA Fiber (L) 10/125um PMDC Fiber (O), 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)		
	ASE Guide Out (Y/X Type)	Same Fiber, Corr. SM Fiber or MM Fiber		
Fiber Tensile Load	N	5		
Max. Optical Power (CW, ASE+Signal)	W	1, 2, 3, 5, 10, 15, 20, 30, 40, 50, 60, 80, 100		
Max. ASE Optical Power (CW)	W	0.3, 0.5, 1, 2, 3, 4, 5, 10		
Operating Temperature	°C	0~50		
Storage Temperature	°C	-40~85		
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5xL35 (≤5W); ∅6.0xL50 (5~10W)	
	Metal Box	mm	H: L90xW12xH10 (>10W); M: L120xW12xH10 (≤10W)	

- Note:**
- Specifications are for device without connectors; Specifications may change without notice.
  - To add connectors, IL is 0.5dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
  - High ER type can only work in slow axis; Suggest to use Y/X type or H Box if blocked optical power is ≥1W.
  - Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
  - Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
  - Package size may be different for different optical power and configurations.

### ORDERING INFORMATION (PN)

FPBP-1032-NN(C)(C) (C) (C) (C) - HPNN -(NN) -(C) C C NN -CC/CCC												
Bandwidth	Type	ASE Type	ASE Iso	Fwd ASE Fiber	Bwd ASE Fiber	Optical Power	ASE Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
50-5nm	R-High ER	B-Backward	I-High	Y-Same Fiber	Y-Same Fiber	1-1W	1-1W	M-Metal Box	2-PM980Fiber	B- Bare fiber	05-0.5m	N-Without Connector
	Blank for	T-Two-way	Isolation	S-Corr. SM Fiber	S-Corr. SM Fiber	5-5W	5-5W	H-H Box	E-PM1060L Fiber	L- Loose Tube	10-1.0m	FC/APC=FC/APC Connector
	Standard	Blank for Forward	Blank for	N=None	A-105/125um Fiber	10-10W	10-10W	Blank for SST	Q=20/130 PMDC Fiber	2- 2mm Cable	15-1.5m	LC/PC=LC/PC Connector
			Standard	Blank for D Type	Blank for None or D Type	20-20W	Blank for 300mW		R=25/250 PMDC Fiber	3- 3mm Cable	20-2.0m	SC/UPC=SC/UPC Connector