

## 1528.7nm PM Bandpass Filter

### FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

### APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Laser Systems
- Research Labs



### SPECIFICATIONS

Parameters		Unit	Standard	High ER Type
Center Wavelength		nm	1528.7	
Min. Pass Band Width @ 0.5dB		nm	0.3, 0.7, 6.0	
Insertion Loss over Pass Band Wavelength		dB	≤1.0	≤1.2
Stop Wavelength (ASE)	0.3nm Bandwidth	nm	1500~1527.7 & 1529.7~1600	
	0.7nm Bandwidth	nm	1500~1527.2 & 1530.2~1600	
	6nm Bandwidth	nm	1500~1523.7 & 1533.7~1600	
Stop Wavelength (ASE)	Standard	dB	≥25	
Isolation	High Isolation	dB	≥45	
ASE Direction		-	F: Forward, B: Backward, T: Two-way	
Configuration		-	D: 2-port, Y: 3-port, X: 4-port	
Optical Return Loss		dB	≥50	
Extinction Ratio		dB	≥18	≥20
Fiber Type	Input&Output	-	PM1550 Panda Fiber or 10/125um PMDC Fiber NA=0.08 (O)	
		-	10/130um PMDC Fiber NA=0.15 (O2) or 12/130um PMDC Fiber (T)	
	-	25/250um PMDC Fiber (R) or 25/300um PMDC Fiber (G)		
	ASE Guide Out (Y/X Type)	-	Same Fiber, Corr. SM Fiber or MM Fiber	
Fiber Tensile Load		N	5	
Max. Average Optical Power (ASE+Signal)		mW	300	
Operating Temperature		°C	0~70	
Storage Temperature		°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5x <sup>L</sup> 35	
	Metal Box	mm	L120x <sup>W</sup> 12x <sup>H</sup> 10	

**Note:** 1. Specifications are for device without connectors; Specifications may change without notice.

2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.

3. High ER type can only work in slow axis.

4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

5. Package size may be different for different optical power and configurations.

### ORDERING INFORMATION (PN)

Bandwidth	Type	ASE Type	ASE Iso	Fwd ASE Fiber	Bwd ASE Fiber	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
03-0.3nm	R=High ER	B=Backward	I=High	Y=Same Fiber	Y=Same Fiber	M=Metal Box	2=PM1550Fiber	B= Bare fiber	05=0.5m	N=Without Connector
07-0.7nm	Blank for	T=Two-way	Isolation	S=Corr. SM Fiber	S=Corr. SM Fiber	Blank for SST	0=10/125 PMDC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
60-6nm	Standard	Blank for Forward	Blank for	N=None	A=105/125um Fiber		T=12/130 PMDC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
			Standard	Blank for D Type	Blank for None or D Type		G=25/300 PMDC Fiber	3= 3mm Cable	20=2.0m	SC/UFC=SC/UFC Connector

