

## 1541.35nm High Power PM Bandpass Filter

### FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

### APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Laser Systems
- Research Labs



### SPECIFICATIONS

Parameters		Unit	Standard	High ER Type
Center Wavelength		nm	1541.35	
Min. Pass Band Width @ 0.5dB		nm	0.12, 0.3, 0.7, 2.0, 15.0, 50	
Insertion Loss over Pass Band Wavelength		dB	≤1.0	≤1.2
Stop Wavelength (ASE)	0.12nm Bandwidth	nm	1500~1540.35 & 1542.35~1600	
	0.3nm Bandwidth	nm	1500~1540.35 & 1542.35~1600	
	0.7nm Bandwidth	nm	1500~1539.85 & 1542.85~1600	
	2nm Bandwidth	nm	1500~1538.35 & 1544.35~1600	
	15nm Bandwidth	nm	1500~1529.35 & 1553.35~1600	
	50nm Bandwidth	nm	1470~1506.35 & 1576.35~1610	
Stop Wavelength (ASE)	Standard	dB	≥25	
Isolation	High Isolation	dB	≥45	
ASE Direction		-	F: Forward, B: Backward, T: Two-way	
Configuration		-	D: 2-port, Y: 3-port, X: 4-port	
Optical Return Loss		dB	≥50	
Extinction Ratio		dB	≥18	≥20
Fiber Type	Input&Output	-	PM1550 Panda Fiber or 10/125um PMDC Fiber NA=0.08 (O) 10/130um PMDC Fiber NA=0.15 (O2) or 12/130um PMDC Fiber (T) 25/250um PMDC Fiber (R) or 25/300um PMDC Fiber (G)	
	ASE Guide Out (Y/X Type)	-	Same Fiber, Corr. SM Fiber or MM Fiber	
Fiber Tensile Load		N	5	
Max. Optical Power (CW, ASE+Signal)		W	1, 2, 3, 5, 10, 15, 20, 30, 40, 50, 60, 80, 100	
Max. ASE Optical Power (CW)		W	0.3, 0.5, 1, 2, 3, 4, 5, 10	
Operating Temperature		°C	0~70	
Storage Temperature		°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5xL35 (≤5W); ∅6.0xL50 (5~10W)	
	Metal Box	mm	H: L90x <sup>W</sup> 12x <sup>H</sup> 10 (>10W); M: L120x <sup>W</sup> 12x <sup>H</sup> 10 (≤10W)	

- Note:**
- Specifications are for device without connectors; Specifications may change without notice.
  - To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
  - High ER type can only work in slow axis; Suggest to use Y/X type or H Box if blocked optical power is ≥1W.
  - Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
  - Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
  - Package size may be different for different optical power and configurations.

### ORDERING INFORMATION (PN)

FPBP-1541.35-NN(C)(C)(C) - (C)

(C) -HP NN -(NN) -(C) C C NN - CC/CCC

Bandwidth	Type	ASE Type	ASE Iso	Fwd ASE Fiber	Bwd ASE Fiber	Optical Power	ASE Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
03-0.3nm	R-High ER	B-Backward	I-High	Y-Same Fiber	Y-Same Fiber	1-1W	1-1W	M-Metal Box	2-PM1550Fiber	B- Bare fiber	05-0.5m	N-Without Connector
07-0.7nm	Blank for	T-Two-way	Isolation	S-Corr. SM Fiber	S-Corr. SM Fiber	5-5W	5-5W	H-H Box	0-10/125 PMDC Fiber	L- Loose Tube	10-1.0m	FC/APC=FC/APC Connector
20-2nm	Standard	Blank for Forward	Blank for	N=None	A=105/125um Fiber	10-10W	10-10W	Blank for SST	T=12/130 PMDC Fiber	2- 2mm Cable	15-1.5m	LC/PC=LC/PC Connector
150-15nm		Standard	Blank for D Type	Blank for D Type	Blank for None or D Type	20-20W	Blank for 300mW		G-25/300 PMDC Fiber	3- 3mm Cable	20-2.0m	SC/UPC=SC/UPC Connector

