

1950nm High Power PM Bandpass Filter

FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Laser Systems
- Research Labs



SPECIFICATIONS

Parameters	Unit	Standard	High ER Type	
Center Wavelength	nm	1950		
Min. Pass Band Width @ 0.5dB	nm	10.0		
Insertion Loss over Pass Band Wavelength	dB	≤1.4	≤1.6	
Stop Wavelength (ASE)	nm	1900-1940 & 1960-2050		
Stop Wavelength (ASE) Standard	dB	≥25		
Isolation High Isolation	dB	≥45		
ASE Direction	-	F: Forward, B: Backward, T: Two-way		
Configuration	-	D: 2-port, Y: 3-port, X: 4-port		
Optical Return Loss	dB	≥50		
Extinction Ratio	dB	≥18	≥20	
Fiber Type	Input&Output	PM1550 Panda Fiber or PM1950 Fiber (V)		
	ASE Guide Out (Y/X Type)	10/130um PMDC Fiber (O) or 25/250um PMDC Fiber (R)		
	ASE Guide Out (Y/X Type)	Same Fiber, Corr. SM Fiber or MM Fiber		
Fiber Tensile Load	N	5		
Max. Optical Power (CW, ASE+Signal)	W	1, 2, 3, 5, 10, 15, 20		
Max. ASE Optical Power (CW)	W	0.3, 0.5, 1, 2, 3, 4, 5, 10		
Operating Temperature	°C	0~50		
Storage Temperature	°C	-40~85		
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5x ^L 35 (≤5W); ∅6.0x ^L 50 (5~10W)	
	Metal Box	mm	H: ^L 90x ^W 12x ^H 10 (>10W); M: ^L 120x ^W 12x ^H 10 (≤10W)	

- Note:**
- Specifications are for device without connectors; Specifications may change without notice.
 - To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 - High ER type can only work in slow axis; Suggest to use Y/X type or H Box if blocked optical power is ≥1W.
 - Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 - Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 - Package size may be different for different optical power and configurations.

ORDERING INFORMATION (PN)

Bandwidth	Type	ASE Type	ASE Iso	Fwd ASE Fiber	Bwd ASE Fiber	Optical Power	ASE Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
100-10nm	R=High ER	B=Backward	I=High	Y=Same Fiber	Y=Same Fiber	1-1W	1-1W	M=Metal Box	2=PM1550Fiber	B= Bare fiber	05=0.5m	N=Without Connector
	Blank for	T=Two-way	Isolation	S=Corr. SM Fiber	S=Corr. SM Fiber	3=3W	5=5W	H=H Box	V=PM1950 Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
	Standard	Blank for Forward	Blank for	N=None	A=105/125um Fiber	5=5W	10=10W	Blank for SST	O=10/130 PMDC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
		Standard	Blank for D Type	Blank for D Type	Blank for None or D Type	10=10W	Blank for 300mW		R=25/250 PMDC Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector