

760-850/1020~1150nm Fused PM WDM Coupler for Pulse Power

FEATURES

- ▣ Low Excess Loss
- ▣ Variety Coupling Ratio
- ▣ Epoxy-Free Optical Path
- ▣ High Reliability and Stability
- ▣ Low Profile Packaging

APPLICATIONS

- ▣ LAN WAN Systems
- ▣ Signal Monitoring
- ▣ Network Monitoring
- ▣ CATV
- ▣ Test Equipments



SPECIFICATIONS

Parameter	Unit	Value	
Center Wavelength 1	nm	760±2, 780±2, 793±2, 808±2, 830±2, 850±2	
Center Wavelength 2	nm	1020±2, 1030±2, 1040±2, 1053±2, 1064±2, 1070±2, 1080±2, 1092±2, 1120±2, 1150±2	
Insertion Loss	dB	≤1.0	
Isolation	dB	≥13	
Extinction Ratio	dB	≥18	
Optical Return Loss	dB	≥40	
Directivity	dB	≥50	
Fiber Type	-	PM780-HP Fiber(7), PM850 Fiber, PM980 Fiber (H) PM1060L Fiber (E) or 10/125um PMDC Fiber (O) NA=0.075	
Fiber Tensile Load	N	5	
Maximum Average Power	W	0.3, 0.5, 1, 2, 3, 5, 10, 15, 20, 25, 30	
Max. Peak Power for Pulse	kW	0.1, 1, 2, 3, 5, 10, 15, 20	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	Φ3.0xL60 for Bare Fiber
	Metal Box		Φ3.0xL76 for 900um Loose Tube
			L120xW12xH10 for 2mm/3mm Cable

Note: 1. Specifications are for device without connectors; Specifications may change without notice.

2. To add connectors, IL is 0.7dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.

3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.

4. 750~850nm may transmit as low order modes in signal fiber.

5. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

6. Package size may be different for different optical power and fiber type.

ORDERING INFORMATION (PN)

FPCD-NN	NN	-N	(C)	(C)	-H NN	P NN	-(C)	(C)	C	NN	-CC/CCC
Wavelength1	Wavelength2	Configuration	Mode	Fiber(λ1)	Average Power	Peak Power	Package	Fiber (Conn&λ2)	Fiber Sleeve	Fiber Length	Connector Type
78-780nm	03-1030nm	1-1x2 Type	M- Mux	S- Corr. SM Fiber	03-300mW	01-100W	M-Metal Box	7- PM780-HP Fiber	B- Bare Fiber	05-0.5m	N-Without Connector
79-793nm	06-1064nm	2-2x2 Type	D- Demux	7- PM780-HP Fiber	5-5W	5-5kW	Blank for SST	H- PM980 Fiber	L- Loose Tube	10-1.0m	FC/APC=FC/APC Connector
83-830nm	83-830nm		Blank for Both	I-HI780 Fiber	10-10W	10-10kW		O- 10/130um PMDC Fiber	2- 2mm Cable	15-1.5m	LC/PC=LC/PC Connector
85-850nm	85-850nm			Blank for Same Fiber	30-30W	20-20kW		Blank for PM850 Fiber	3- 3mm Cable	20-2.0m	SC/UPC=SC/UPC Connector