

750~850nm PM Fused Splitter Module (1x4, 1x8, 2x4, 2x8)

FEATURES

- Low Excess Loss
- Various Splitting Ratio
- Wide Passband
- High Stability and Reliability
- Epoxy Free Optical Path

APPLICATIONS

- Optical Amplifier
- Optical Networks
- Power Monitoring
- Fiber Sensor
- Lab

SPECIFICATIONS

Parameter	Unit	1x4, 2x4, 4x4	1x8, 2x8, 4x8
Center Wavelength	nm	750, 780, 793, 808, 830, 850	
Bandwidth	nm	+/-10	
Insertion Loss	Typ.	7.3	10.8
	Max.	7.8	11.5
Uniformity	dB	1.2	1.6
Extinction Ratio	dB	≥18	≥16
Optical Return Loss	dB	≥40	
Directivity	dB	≥45	
Fiber Type	-	PM850 Panda Fiber or PM780-HP Fiber	
Fiber Tensile Load	N	5	
Max. Optical Power (CW)	mW	300	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	mm	(L)160x(W)140x(H)10	(L)160x(W)160x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.7dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FPCM-	NNN	-	NxN	- (C)	C	NN	-CC/CCC
	Wavelength		Configuration	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
	850-850nm		1X4-1X4 Type	7-PM780HP Fiber	B- Bare fiber	05-0.5m	N-Without Connector
	830-830nm		1X8-1X8 Type	Blank for PM850 Fiber	L- Loose Tube	10-1.0m	FC/APC=FC/APC Connector
	808-808nm		2X4-2X4 Type		2- 2mm Cable	15-1.5m	LC/PC=LC/PC Connector
	780-780nm		2X8-2X8 Type		3- 3mm Cable	20-2.0m	SC/UPC=SC/UPC Connector