

## 900~950nm Single Fiber PM Collimator for Pulse Power

### FEATURES

- High Return Loss
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability
- Low Profile Packaging

### APPLICATIONS

- Optical Isolator
- Optical Circulator
- Optical Components
- WDM Assembly
- Laboratory R&D



### SPECIFICATIONS

Parameters	Unit	Single Fiber
Working Wavelength	nm	915, 930, 940, 950
Bandwidth	nm	+/-10
Working Distance (WD)	mm	5, 10, 15, 20, 30, 50
Insertion Loss (WD=5mm)	Typ.	dB
	Max.	dB
Return Loss	dB	≥50
Lens Type	-	C-Lens, GRIN Lens or Aspherical-Lens
Extinction Ratio	Typ.	dB
	Min.	dB
Fiber Type	-	PM780-HP Fiber (7), PM850 Fiber, PM980 Fiber or PM1060L Fiber (E) 10/125um PMDC Fiber (O), 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)
Fiber Length	m	1.0, 1.5 or customer specify
Max. Average Optical Power	W	0.3, 0.5, 1, 2, 3, 5, 10, 20, 30, 40, 50, 60, 80, 100
Max. Peak Power for pulse	kW	0.1, 1, 2, 3, 5, 10, 15, 20
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	mm	Φ3.2x <sup>L</sup> 10 for Metal Tube Φ2.78x <sup>L</sup> 9 for Glass Tube

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
  2. To add connectors, IL is 0.7dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
  3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
  4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
  5. Package size may be different for different lens and optical power.

### ORDERING INFORMATION (PN)

FPCO- NNN	-S NNN	- C	C	C	-H NN	P NN	- C	C	NN	- CC/CCC
Wavelength	WD	Package	Housing	Lens	Average Power	Peak Power	Fiber Type	Fiber Sleeve	Fiber Length	Connector
915-915nm	005= 5mm	S= Standard	M= Metal	G=Grin Lens	03=300mW	01=100W	2=PM850Fiber	B=Bare Fiber	05=0.5m	N= None
930-930nm	010=10mm		G= Glass	C=C-lens	1= 1W	1= 1kW	H=PM980 Fiber	L=Loose Tube	10=1.0m	SC/PC= SC/PC Connector
940-940nm	020= 20mm			A=Aspherical Lens	5= 5W	5= 5kW	E=PM1060L Fiber		15=1.5m	FC/APC=FC/APC Connector
950-950nm	050= 50mm				10=10W	10=10kW	R=25/250 PMDC Fiber		20=2.0m	LC/UPC=LC/UPC Connector