

1064nm 4-port PM Optical Circulator for Pulse Power



FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Fiber Optic Amplifiers
- Fiber Optic Instruments
- WDM Systems
- Dispersion Compensation
- Light Routing

SPECIFICATIONS

Parameter	Unit	A Type	B Type	
Center Wavelength	nm	1064		
Operating Wavelength Range	nm	+/-5		
Optical Path	-	1→2, 2→3, 3→4	1→2, 2→3, 3→4, 4→1	
Insertion Loss @ 23°C	(Typ.)	dB	3.8	2.4
	(Max.)	dB	4.2	2.8
Isolation @ 23°C	(Typ.)	dB	45	26
	(Min.)	dB	40	20
Cross Talk	dB	≥50		
Optical Return Loss	dB	≥50		
Extinction Ratio	(Typ.)	dB	23	20
	(Min.)	dB	20	18
Polarization Alignment	-	Slow Axis		
Fiber Type	-	PM980 Fiber, PM1060L Fiber (E) or PM1060L-FA Fiber (L) 10/125um PMDC Fiber (O), 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)		
Fiber Tensile Load	N	5		
Maximum Average Power	mW	300		
Max Peak Power for Pulse	kW	0.1, 1, 2, 3, 5, 10, 15, 20		
Operating Temperature	°C	0~50		
Storage Temperature	°C	-40~85		
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5x35	
	Metal Box	mm	L120xW12xH10	

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.5dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. The devices can only work in slow axis and fast axis is blocked.
 4. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 5. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device

ORDERING INFORMATION (PN)

FPCR-NNNN	-4	C	-	H NN	P NN	- (C)	C	C	NN	-CC/CCC
<i>Center Wavelength</i>	<i>Type</i>	<i>Average Power</i>	<i>Peak Power</i>	<i>Package</i>	<i>Fiber Type</i>	<i>Fiber Sleeve</i>	<i>Fiber Length</i>	<i>Connector Type</i>		
1064=1064nm	A=A Type B=B Type	03=300mW	01=100W 1=1kW 5=5kW 10=10kW	M=Metal Box Blank for SST	2=PM980Fiber E=PM1060L Fiber Q=20/130 PMDC Fiber R=25/250 PMDC Fiber	B= Bare Fiber L= Loose Tube 2= 2mm Cable 3= 3mm Cable	05=0.5m 10=1.0m 15=1.5m 20=2.0m	N=Without Connector FC/APC=FC/APC Connector LC/PC=LC/PC Connector SC/UPC=SC/UPC Connector		