

3-Port Optical Circulator with Both Axis Working

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Fiber Optic Amplifiers
- Fiber Optic Instruments
- WDM Systems
- Dispersion Compensation
- Light Routing



SPECIFICATIONS

Configuration	Unit	3-port	
Working Wavelength	nm	1295-1325, 1470-1490 1525-1565, 1580-1600	
Insertion Loss	(Typ.)	1.0	
	(Max.)	1.2	
Isolation	(Min.)	30	
Optical Return Loss	dB	≥45	
Cross Talk	dB	≥45	
Extinction Ratio	dB	≥18	
Work Mode	-	F Type, Can work both in slow axis and fast axis	
Fiber Type	-	PM1310/1550 Panda Fiber, 10/125um PMDC Fiber NA=0.08 (O)	
		10/130um PMDC Fiber NA=0.15 (O2), 12/130um PMDC Fiber (T)	
		25/250um PMDC Fiber (R), 25/300um PMDC Fiber (G)	
Fiber Tensile Load	N	5	
Max. Optical Power (CW)	mW	300	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5x50
	Metal Box	mm	L120xW12xH10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 5. Package size may be different for different fiber types

ORDERING INFORMATION (PN)

FPCR-	NNNN	-F3- (C)	C	C	NN	- CC/CCC
Center Wavelength	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type	
1310-1310nm	M-Metal Box	2-PM1310/1550 Fiber	B- Bare Fiber	05-0.5m	N-Without Connector	
1480-1480nm	Blank for SST	0-10/125 PMDC Fiber	L- Loose Tube	10-1.0m	FC/APC=FC/APC Connector	
1550-1550nm		T-12/130 PMDC Fiber	2- 2mm Cable	15-1.5m	LC/PC=LC/PC Connector	
1590-1590nm		R-25/250 PMDC Fiber	3- 3mm Cable	20-2.0m	SC/UPC=SC/UPC Connector	