

## 750~850nm PM Filter Splitter Module

### FEATURES

- Low Excess Loss
- Various Splitting Ratio
- Wide Passband
- High Stability and Reliability
- Epoxy Free Optical Path

### APPLICATIONS

- Optical Amplifier
- Optical Networks
- Power Monitoring
- Fiber Sensor
- Lab



### SPECIFICATIONS

Parameter	Unit	1x4 or 2x4 or 4x4	1x8 or 2x8 or 4x8
Center Wavelength	nm	750, 780, 793, 808, 830, 850	
Bandwidth	nm	+/-15nm or customer specify	
Insertion Loss	Typ.	dB	7.5
	Max.	dB	8.1
Uniformity	dB	≤1.0	≤1.2
Extinction Ratio	B Type	dB	≥20
	F Type	dB	≥22
Working Mode	B Type	dB	Can work both in Fast Axis and Slow Axis
	F Type	dB	Can only work in Slow Axis and Fast Axis is blocked
Optical Return Loss	dB	≥50	
Directivity	dB	≥50	≥45
Fiber Type	-	PM850 Panda Fiber or PM780-HP Fiber	
Fiber Tensile Load	N	5	
Max. Optical Power (CW)	mW	300	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	mm	(L)160x(W)140x(H)10	(L)160x(W)160x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
  2. To add connectors, IL is 0.7dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
  3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

### ORDERING INFORMATION (PN)

<b>FPFM -</b>	<b>NNN</b>	<b>-</b>	<b>NxN</b>	<b>(C)</b>	<b>-</b>	<b>C</b>	<b>C</b>	<b>NN</b>	<b>-</b>	<b>CC/CCC</b>
	<i>Wavelength</i>		<i>Configuration</i>	<i>Type</i>		<i>Fiber Type</i>	<i>Fiber Sleeve</i>	<i>Fiber Length</i>		<i>Connector Type</i>
	780~780nm		1X4=1X4 Type	B=B Type		2= PM850 Fiber	B= Bare Fiber	05=0.5m		N=Without Connector
	793~793nm		1X8=1X8 Type	Blank for F Type		7= PM780HP Fiber	L= Loose Tube	10=1.0m		FC/APC=FC/APC Connector
	808~808nm		2X4=2X4 Type				2= 2mm Cable	15=1.5m		LC/PC=LC/PC Connector
	850~850nm		4X8=4X8 Type				3= 3mm Cable	20=2.0m		SC/UPC=SC/UPC Connector