

980/1020-1120nm High Power WDM/Partial Mirror PM Hybrid

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Metro Networks
- CATV Networks



SPECIFICATIONS

Parameters	Unit	Standard Type	High ER Type
Signal Wavelength Range λ_1	nm	1020+/-5, 1030+/-10, 1040+/-10, 1053+/-10, 1064+/-10, 1080+/-10, 1092+/-5, 1120+/-5	
Pump Wavelength Range λ_2	nm	980+/-10	
Excess Loss	Signal Channel@ λ_1	dB	≤ 1.4
Insertion Loss	Pump Channel@ λ_2	dB	≤ 0.8
Signal Reflective Ratio (Common<->Pass)		%	1 \pm 0.6, 2 \pm 0.8, 5 \pm 1, 10, 20, 30, 40, 50, 60, 70, 80, 90
Wavelength	Signal Channel@ λ_2	dB	≥ 25
Isolation	Pump Channel@ λ_1	dB	≥ 12
Optical Return Loss		dB	≥ 45
Extinction Ratio		dB	≥ 18
Pump Type	Forward	-	Pump&Signal at same direction
	Backward	-	Pump&Signal at reverse direction
Fiber Type	Common & Signal Port	-	PM980 Fiber, PM1060L Fiber (E) or PM1060L-FA Fiber (L) 10/125um PMDC Fiber (O), 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)
	Pump Port	-	Same Fiber or Corresponding SM Fiber
Fiber Tensile Load		N	5
Maximum Optical Power (CW)		W	1, 2, 3, 5, 10, 15, 20
Operating Temperature		°C	0~50
Storage Temperature		°C	-40~85
Package Dimension	Stainless Steel Tube (SST)	mm	(\varnothing)5.5x40 (\leq 5W); (\varnothing)6.0x48 (5~10W)
	Metal Box	mm	(L)90x(W)18x(H)10 (>10W); (L)120x(W)12x(H)10 (\leq 10W)

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.5dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 5. High ER type can only work in slow axis at pass port.

ORDERING INFORMATION (PN)

FPHP-98NN - (C)	NN	C	(C) -HP NN	-(C)	C	C	NN	-CC/CCC		
Pass Wavelength	Pump Type	Tap Ratio	Pump Fiber	Type	Optical Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
06=1064nm	F=Forward	01=1%	P=Same Fiber	H=High ER	1=1W	M=Metal Box	2=PM980Fiber	B= Bare fiber	05=0.5m	N=Without Connector
03=1030nm	Blank for Backward	05=5%	S=Corr. SM Fiber	Blank for Standard	5=5W	Blank for SST	E=PM1060L Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
08=1080nm		10=10%			10=10W	or >10W	Q=20/130 PMDC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
12=1120nm		50=50%			20=20W		R=25/250 PMDC Fiber	3= 3mm Cable	20=2.0m	SC/UFC=SC/UFC Connector