



1290nm PM BP/Partial Mirror Hybrid

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Metro Networks
- CATV Networks

SPECIFICATIONS

Parameters	Unit	Standard	High ER Type	
Center Wavelength	nm	1290		
Min. Bandwidth@0.5dB	nm	15.0		
Excess Loss	dB	≤1.3	≤1.5	
Stop Band @25dB	nm	1250~1278 & 1304-1360		
Reflective Ratio	%	1±0.6, 2±0.8, 5±1, 10, 20, 30, 40, 50, 80, 90		
Configuration	D Type	2-port		
	Y Type	3-port, (Blocked Wavelength Guide Out)		
Fiber Type at 3 rd Port (Only for Y Type)	-	Same Fiber, Corr. SM Fiber or 50/125um MM Fiber		
Optical Return Loss	dB	≥45		
Extinction Ratio	dB	≥18	≥20	
Fiber Type	-	PM1310 Panda Fiber, 10/125um PMDC Fiber (O),		
		12/130um PMDC Fiber (T), 20/130um PMDC Fiber (Q)		
		25/250um PMDC Fiber (R), 25/300um PMDC Fiber (G)		
Fiber Tensile Load	N	5		
Max. Optical Power (CW)	mW	300		
Operating Temperature	°C	0~50		
Storage Temperature	°C	-40~85		
Package Dimension	Stainless Steel Tube (SST)	mm	(Ø)5.5x35	
	Metal Box	mm	(L)120x(W)12x(H)10	

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. High ER type can only work in slow axis at pass port; Suggest to use Y type if blocked optical power is >1W.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

Center Wavelength	Bandwidth	Ref. Ratio	Type	3rd Port Fiber	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
1290-1290nm	150-15nm	01= 1%	R=High ER	Y=Same Fiber	M=Metal Box	2=PM1310Fiber	B= Bare fiber	05=0.5m	N=Without Connector
		05=5%	Blank for	S=Corr. SM Fiber	Blank for SST	0=10/125 PMDC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
		50=50%	Standard	5=50/125um Fiber		T=12/130 PMDC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
		90=90%		Blank for D Type		G=25/300 PMDC Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector