


1030nm Mini-Size Polarization Maintaining Isolator

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Fiber Optic Amplifiers
- Fiber Optic Instruments
- WDM Systems
- Transmitters and Fiber Lasers
- CATV Networks



SPECIFICATIONS

Parameter	Unit	Single Stage	Dual Stage
Center Wavelength (λ_c)	nm	1030	
Bandwidth	nm	+/-10	
Peak Isolation (Typ.)	dB	25	45
Isolation (λ_c +/-10nm, 23°C)	dB	≥20	≥40
Insertion Loss (λ_c , 23°C)	dB	3.0	5.0
Insertion Loss (λ_c , 0-50°C)	dB	≤4.0	≤7.8
Optical Return Loss (Input/Output)	dB	50/45	50/45
Extinction Ratio	dB	≥20	
Working Mode	S Type	-	Can only work in Slow Axis
	F Type	-	Can work both in Slow Axis and Fast Axis
Fiber Type	-	PM980 Fiber, PM1060L Fiber (E) or PM1060L-FA Fiber (L) 10/125um PMDC Fiber (O), 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)	
Fiber Tensile Load	N	5	
Maximum Optical Power (CW)	mW	50	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	mm	(Φ)3.0x20	

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.5dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FPIM-	NNNN	-	C	C	-	C	C	NN	-	CC/CCC
<i>Center Wavelength</i>			<i>Stage</i>	<i>Type</i>		<i>Fiber Type</i>	<i>Fiber Sleeve</i>	<i>Fiber Length</i>		<i>Connector Type</i>
1030=1030nm			S= Single Stage	S= S Type		2=PM980 Panda Fiber	B= Bare fiber	05=0.5m		N=Without Connector
			D= Dual Stage	F= F Type		E=PM1060L Fiber	L= Loose Tube	10=1.0m		FC/APC=FC/APC Connector
						Q=20/130 PMDC Fiber	2= 2mm Cable	15=1.5m		LC/PC=LC/PC Connector
						R=25/250 PMDC Fiber	3= 3mm Cable	20=2.0m		SC/UPC=SC/UPC Connector