

1092nm PM Isolator for Pulse Power

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Fiber Optic Amplifiers
- Fiber Optic Instruments
- WDM Systems
- Transmitters and Fiber Lasers
- CATV Networks



SPECIFICATIONS

Parameter	Unit	Single Stage	Dual Stage
Center Wavelength (λ_c)	nm	1092	
Bandwidth	nm	+/-10	
Peak Isolation (Typ.)	dB	25	45
Isolation ($\lambda_c \pm 5\text{nm}$, 23°C)	dB	≥ 22	≥ 40
Insertion Loss (λ_c , 23°C)	dB	1.7	2.6
Insertion Loss (λ_c , 0-50°C)	dB	≤ 2.2	≤ 3.6
Optical Return Loss (Input/Output)	dB	50/45	50/45
Extinction Ratio	dB	≥ 18	
Working Mode	S Type	-	Can only work in Slow Axis
	F Type	-	Can work both in Slow Axis and Fast Axis
Fiber Type	-	PM980 Fiber, PM1060L Fiber (E) or PM1060L-FA Fiber (L) 10/125um PMDC Fiber (O), 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)	
Fiber Tensile Load	N	5	
Max. Average Optical Power	mW	300	
Max. Peak Power for pulse	kW	0.1, 1, 2, 3, 5, 10, 15, 20	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	(\varnothing)5.5x35
	Metal Box	mm	(L)120x(W)12x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.5dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FPIS-NNNN	-	C	C	-	H	NN	P	NN	-	(C)	C	C	NN	-	CC/CCC
<i>Center Wavelength</i>		<i>Stage</i>	<i>Type</i>		<i>Average Power</i>	<i>Peak Power</i>		<i>Package</i>		<i>Fiber Type</i>	<i>Fiber Sleeve</i>		<i>Fiber Length</i>		<i>Connector Type</i>
1092-1092nm		S- Single Stage	S- S Type		03-300mW	01-100W		M-Metal Box		2-PM980 Fiber	B- Bare fiber		05-0.5m		N-Without Connector
		D- Dual Stage	F- F Type			1- 1kW		Blank for SST		E-PM1060L Fiber	L- Loose Tube		10-1.0m		FC/APC=FC/APC Connector
						5-5kW				Q-20/130 PMDC Fiber	2- 2mm Cable		15-1.5m		LC/PC=LC/PC Connector
						10-10kW				R-25/250 PMDC Fiber	3- 3mm Cable		20-2.0m		SC/UPC=SC/UPC Connector