

900~950nm High Power PM Optical Isolator

FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

APPLICATIONS


- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Laser Systems
- Research Labs

SPECIFICATIONS

Parameter	Unit	High Power Type
Center Wavelength (λ_c)	nm	915, 930, 940, 950
Operating Wavelength Range	nm	+/-10
Peak Isolation (Typ.)	dB	25
Min. Isolation (23°C)	dB	20
Typical Insertion Loss (λ_c , 23°C)	dB	1.3
Max. Insertion Loss (λ_c , 23°C)	dB	1.8
Optical Return Loss (Input/Output)	dB	45/45
Extinction Ratio (Min.)	dB	18
Working Mode	S Type	-
	F Type	-
Configuration	-	Can only work in Slow Axis Can work both in Slow Axis and Fast Axis
Fiber Type	Input&Output	-
		Standard: 2-Port; Y Type: 3-Port, Backward Power Guide Out
	3 rd Port (Y Type)	-
Fiber Tensile Load	N	5
Maximum Optical Power (CW)	W	1, 2, 3, 5, 10, 15, 20, 30, 40, 50, 60, 80, 100
Max. Backward Optical Power (CW)	W	0.3, 0.5, 1, 2, 3, 5, 10
Operating Temperature	°C	0~50
Storage Temperature	°C	-20~75

- Note:**
- Specifications are for device without connectors; Specifications may change without notice.
 - To add connectors, IL is 0.7dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 - Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 - Suggest to use Y type for >20W Optical Power or continuous backward power of $\geq 500\text{mW}$.
 - Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 - Package dimensions may be different for different fiber type, optical power and configuration.

PACKAGE DIMENSION



ORDERING INFORMATION (PN)

FPIS-NNNN	-C	(C)	HP NN	- (NN)	- C	C	NN	-CC/CCC
Center Wavelength	Type	3 rd Port Fiber	Optical Power	Backward Power	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
915~915nm	S= S Type	Y= Same Fiber	1=1W	05=500mW	2=PM850Fiber	B= Bare Fiber	05=0.5m	N=Without Connector
930~930nm	F= F Type	A=105/125um Fiber	3=3W	1=1W	H=PM980 Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
940~940nm		Blank for Standard	10=10W	10=10W	E=PM1060L Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
950~950nm			100=100W	Blank for 300mW	R=25/250 PMDC Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector

