

# 1070nm Inline Faraday Rotator with Phase Bias for Pulse Power

## FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path

## APPLICATIONS

- Fiber Optic Amplifiers
- Sensing Systems
- Telecommunication Networks

## SPECIFICATIONS

Parameter	Unit	Value	
Center Wavelength (CW)	nm	1070	
Bandwidth	nm	+/-5	
Insertion Loss	dB	≤1.9 (Type B), ≤3.4 (Type A)	
Rotate Angle (Single Transmission)	A: FR+WP+FR B: WP+FR	deg deg	90 (Backward Signal to Slow axis of Input Fiber) 45 (Backward Signal to Fast axis of Input Fiber)
Rotation Angle Tolerance (CW. 23°C)	Deg	≤+/-4	
Phase Bias between Forward and Backward	-	$\pi$ , $\pi/2$ , $\pi/4$ or specify	
Return Loss	dB	≥50	
PDL (for SM Fiber Type)	dB	≤0.2	
Extinction Ratio (for PM Fiber Type)	Standard High ER Type	dB dB	≥18 ≥20 (Can only work in Slow Axis)
Fiber Type	SM Fiber Type PM Fiber Type	- -	HI1060 Fiber or 10/125um SC Fiber (E) 10/125um DC Fiber (O), 15/130um DC Fiber (W) 20/130um DC Fiber (Q) or 25/250um DC Fiber (R) PM980 Fiber, PM1060L Fiber (E) or PM1060L-FA Fiber (L) 10/125um PMDC Fiber (O), 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)
Fiber Tensile Load	N	5	
Max. Average Power (Forward+Backward)	mW	300	
Max. Peak Power for pulse	kW	0.1, 1, 2, 3, 5, 10, 15, 20	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST) Metal Box	mm mm	(Ø)5.5x35 (L)120x(W)12x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
  2. To add connectors, IL is 0.5dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
  3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
  4. Forward/backward signals transmit through fast axis/slow axis of a waveplate induces the phase bias.
  5. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

## ORDERING INFORMATION (PN)

<b>FRPB-NNNN</b>	-	<b>C</b>	<b>N</b>	<b>(C)</b>	<b>C</b>	<b>C-H03PNN</b>	<b>-(C)</b>	<b>(C)</b>	<b>C</b>	<b>NN</b>	<b>-CC/CCC</b>
<i>Center Wavelength</i>	<i>Rotate Angle</i>	<i>Phase Bias</i>	<i>Type</i>	<i>Input Fiber</i>	<i>Output Fiber</i>	<i>Peak Power</i>	<i>Package</i>	<i>Fiber Type</i>	<i>Fiber Sleeve</i>	<i>Fiber Length</i>	<i>Connector Type</i>
1070=1070nm	A=90	1=π	R=High ER	S=SM Fiber	S=SM Fiber	01=100W	M=Metal Box	E=10/125 SC or PM1060L Fiber	B= Bare Fiber	05=0.5m	N=Without Connector
	B=45	2=π/2	Blank for	P= PM Fiber	P= PM Fiber	1= 1kW	Blank for SST	Q=20/130 DC or PMDC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
		4=π/4	Standard			5= 5kW		R=25/250 DC or PMDC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
						10=10kW		Blank for HI1060 or PM980 Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector