

900~960nm Singlemode Pump Laser Protector

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Metro Networks
- CATV Networks



SPECIFICATIONS

Parameters	Unit	Standard	High Isolation	
Pump Laser Center Wavelength	nm	915, 930, 940, 950		
Pump Laser Bandwidth	nm	+/-15		
Blocking Signal Wavelength	Type 6	1020~1120		
	Type 4	1000~1120		
	Type 5	1500~1620		
	Type 2	1020~1120&1500~1620		
Pump Insertion Loss	Typ.	0.6	0.7	
	Max.	1.0		
Backward Signal Attenuation	Typ.	≥25	≥50	
Configuration	D Type	2-port		
	Y Type	3-port, (Backward Power Guide Out)		
Return Loss	dB	≥50		
Fiber Type	Input & Output	HI780 Fiber, HI1060 Fiber or 10/125um SC Fiber (E) 10/125um DC Fiber (O), 15/130um DC Fiber (W) 20/130um DC Fiber (Q) or 25/250um DC Fiber (R)		
	3 rd Port (Only for Y Type)	Same Fiber or 50/125um MM Fiber		
Fiber Tensile Load	N	5		
Max. Optical Power (Pump+Signal, CW)	W	0.3, 0.5, 1, 2, 3, 5, 10, 15, 20		
Max. Signal Power (CW)	W	0.3, 0.5, 1, 2, 3, 5, 10		
Operating Temperature	°C	0~50		
Storage Temperature	°C	-40~85		
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5x ^L 35 (≤5W); ∅6.0x ^L 50 (5~10W)	
	Metal Box	mm	^L 90x ^W 12x ^H 10 (>10W); ^L 120x ^W 12x ^H 10 (≤10W)	

Note: 1. Specifications are for device without connectors; Specifications may change without notice.

2. To add connectors, IL is 0.7dB higher, RL is 5dB lower.

3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.

4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

5. Suggest to use Y type if blocked optical power is >1W.

6. Package size may be different for different optical power, fiber type and configurations.

ORDERING INFORMATION (PN)

Center Wavelength	Type	Isolation	3rd Port Fiber	Optical Power	Signal Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
915= 915nm	4= Type 4	I=High Isolation	Y= Same Fiber	03=300mW	05=500mW	M=Metal Box	H=HI1060 Fiber	B= Bare fiber	05=0.5m	N=Without Connector
930= 930nm	5= Type 5	Blank for Standard	5=50/125um Fiber	1= 1W	1= 1W	Blank for SST	E=10/125 SC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
940= 940nm	2=Type 2		Blank for D Type	5= 5W	5= 5W	or >10W	R=25/250 DC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
950= 950nm	Blank for Type 6			10=10W	Blank for 300mW		Blank for HI780 Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector

