

## 900~960nm Singlemode PM Pump Laser Protector for Pulse

### FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

### APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Metro Networks
- CATV Networks



### SPECIFICATIONS

Parameters	Unit	Standard	High ER Type
Pump Laser Center Wavelength	nm	915, 930, 940, 950	
Pump Laser Bandwidth	nm	+/-15	
Blocking Signal Wavelength	Type 6	1020~1120	
	Type 4	1000~1120	
	Type 5	1500~1620	
	Type 2	1020~1120&1500~1620	
Pump Insertion Loss	dB	≤1.0	≤1.2
Backward Signal Attenuation	Standard	≥25	
	High Isolation	≥50	
Configuration	D Type	2-port	
	Y Type	3-port, (Backward Power Guide Out)	
Return Loss	dB	≥50	
Extinction Ratio	dB	≥18	≥20
Fiber Type	Input & Output	PM850 Fiber, PM980 Fiber or PM1060L Fiber (E) 10/125um PMDC Fiber (O), 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)	
	3 <sup>rd</sup> Port (Only for Y Type)	Same Fiber, Corr. SM Fiber or 50/125um MM Fiber	
Fiber Tensile Load	N	5	
Max. Average Power (Pump+Signal)	W	0.3, 0.5, 1, 2, 3, 5, 10, 15, 20	
Max. Peak Power for Pulse	kW	0.1, 1, 2, 3, 5, 10, 15, 20	
Max. Signal Average Power	W	0.3, 0.5, 1, 2, 3, 5, 10	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	∅5.5x <sup>L</sup> 35 (≤5W); ∅6.0x <sup>L</sup> 50 (5~10W)	
	Metal Box	<sup>L</sup> 90x <sup>W</sup> 12x <sup>H</sup> 10 (>10W); <sup>L</sup> 120x <sup>W</sup> 12x <sup>H</sup> 10 (≤10W)	

- Note:**
- Specifications are for device without connectors; Specifications may change without notice.
  - To add connectors, IL is 0.7dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
  - Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
  - Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
  - High ER type can only work in slow axis; Suggest to use Y type if blocked optical power is >1W.
  - Package size may be different for different optical power, fiber type and configurations.

### ORDERING INFORMATION (PN)

FSPR-NNN (C) - (N) (C) (C) -H NN P NN - (NN) -(C) C C NN -CC/CCC	Center Wavelength	Type	Type	Isolation	3rd Port Fiber	Average Power	Peak Power	Signal Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
915-915nm R-High ER 4-Type 4 I-High Isolation Y-Same Fiber 03-300mW 01-100W 05-500mW M-Metal Box 2-PM850 Fiber B-Bare fiber 05-0.5m N-Without Connector	915-915nm	R-High ER	4-Type 4	I-High Isolation	Y-Same Fiber	03-300mW	01-100W	05-500mW	M-Metal Box	2-PM850 Fiber	B-Bare fiber	05-0.5m	N-Without Connector
930-930nm Blank for Standard 5-Type 5 Blank for Standard S-Corr. SM Fiber 1-1W 1-1kW 1-1W Blank for SST H-PM980 Fiber L-Loose Tube 10-1.0m FC/APC=FC/APC Connector	930-930nm	Blank for Standard	5-Type 5	Blank for Standard	S-Corr. SM Fiber	1-1W	1-1kW	1-1W	Blank for SST	H-PM980 Fiber	L-Loose Tube	10-1.0m	FC/APC=FC/APC Connector
940-940nm 2-Type 2 5-50/125um Fiber 5-5W 5-5kW 5-5W or >10W E-PM1060L Fiber 2-2mm Cable 15-1.5m LC/PC=LC/PC Connector	940-940nm		2-Type 2		5-50/125um Fiber	5-5W	5-5kW	5-5W	or >10W	E-PM1060L Fiber	2-2mm Cable	15-1.5m	LC/PC=LC/PC Connector
950-950nm Blank for Type 6 Blank for D Type 10-10W 10-10kW Blank for 300mW R-25/250 PMDC Fiber 3-3mm Cable 20-2.0m SC/APC=SC/APC Connector	950-950nm	Blank for Type 6		Blank for D Type		10-10W	10-10kW	Blank for 300mW		R-25/250 PMDC Fiber	3-3mm Cable	20-2.0m	SC/APC=SC/APC Connector

